

RL1004-2910-97-D1

uote

RL1004-2910-97-D1 Information

	Part Number	RL1004-2910-97-D1	
	Manufacturer	Amphenol Advanced Sensors	ENATES
www.heiseger.com	Category	Sensors, Transducers Temperature Sensors - NTC Thermistors	
	Description	NTC THERMISTOR 5K OHM 10% DISC	_ ಸ್ಟ್ರಾಟನಿ
	Package	Disc, 2.8mm Dia x 3.0mm W	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL1004-2910-97-D1 Specifications

Manufacturer Part Number RL1004-2910-97-D1 Manufacturer Amphenol Advanced Sensors Category Sensors, Transducers Temperature Sensors - NTC Thermistors Temperature Sensors - NTC Thermistors Package Disc, 2.8mm Dia x 3.0mm W Series RL1004 Resistance in Ohms @ 25°C 5k Resistance Tolerance ±10% B Value Tolerance - B/50 - B/51 - B/52/50 - B/51/10 - D/50 - B/51/10 - Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.0mm W		
CategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 2.8mn Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°CSkResistance Tolerance±10%B Value Tolerance-B0/500B25/50-B25/509/2KB25/503972KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mn Dia x 3.0mm W	Manufacturer Part Number	RL1004-2910-97-D1
Temperature Sensors - NTC ThermistorsPackageDisc, 2.8mm Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°C5kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/503972KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Manufacturer	Amphenol Advanced Sensors
PackageDisc, 2.8mn Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°C5kResistance Tolerance±10%B Value Tolerance-B Value Tolerance-B0/50-B25/50-B25/75-B25/853972KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeDisc, 2.8mn Dia x 3.0mm WPokage / CaseDisc, 2.8mn Dia x 3.0mm W	Category	Sensors, Transducers
Series RL1004 Resistance in Ohms @ 25°C 5k Resistance Tolerance ±10% B Value Tolerance - B Value Tolerance - B0/50 - B25/50 - B25/50 - B25/51 - B25/52 3972K B25/100 - Operating Temperature - Power - Max - Length - Lead Wire 1.50° (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mn Dia x 3.0mm W		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C5kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/553972KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeDisc, 2.8mm Dia x 3.0mm W	Package	Disc, 2.8mm Dia x 3.0mm W
Resistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/853972KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Series	RL1004
B Value Tolerance-B Value Tolerance-B 0/50-B 25/50-B 25/753972KB 25/100-Poperating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeFhrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Resistance in Ohms @ 25°C	5k
B0/50-B25/50-B25/75-B25/853972KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Resistance Tolerance	$\pm 10\%$
B25/50-B25/75-B25/853972KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 2.8mn Diax 3.0mm W	B Value Tolerance	-
B25/75-B25/853972KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Diax 3.0mm W	B0/50	-
B25/85 3972K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.0mm W	B25/50	-
B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Diax 3.0mm W	B25/75	-
Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B25/85	3972K
Power - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B25/100	-
Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Operating Temperature	-50°C ~ 150°C
Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Power - Max	-
Package / CaseDisc, 2.8mm Dia x 3.0mm W	Length - Lead Wire	1.50" (38.00mm)
-	Mounting Type	Through Hole
Report errors?	Package / Case	Disc, 2.8mm Dia x 3.0mm W
		Report errors?

RL1004-2910-97-D1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RL1004-2910-97-D1 Payment Methods



RL1004-2910-97-D1 Shipping Methods



If you have any question about RL1004-2910-97-D1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com