

RL1004-81.1K-138-D1

RL1004-81.1K-138-D1 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL1004-81.1K-138-D1 Specifications

Manufacturer Part NumberRL1004-81.1K-138-D1ManufacturerAmphenol Advanced SensorsCategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 2.8mm Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°C150kResistance Tolerance±10%B Value Tolerance.B0/50.B25/50.B25/75.B25/854561KB25/100.Operating Temperature.50°C ~ 150°CPower - Max.Length - Lead Wire1.50" (38.0mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W		
CategoryAnsars, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 2.8mm Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°C150kResistance Tolerance±10%B Value Tolerance-B0/500.B25/50-B25/50-B25/514561KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Manufacturer Part Number	RL1004-81.1K-138-D1
Temperature Sensors - NTC ThermistorsPackageDisc, 2.8mm Dia x 3.0mm WSeriesRL 1004Resistance in Ohms @ 25°C150kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/75-B25/854561KB25/100-Operating Temperature-Operating Temperature-Power - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeDisc, 2.8mm Dia x 3.0mm W	Manufacturer	Amphenol Advanced Sensors
PackageDisc, 2.8mm Dia x 3.0mm WSeriesRL1004Resistance in Ohms @ 25°C150kResistance Tolerance±10%B Value Tolerance-B/50-B0/50-B25/50-B25/75-B25/854561KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Category	Sensors, Transducers
Series RL1004 Resistance in Ohms @ 25°C 150k Resistance Tolerance ±10% B Value Tolerance - B Value Tolerance - B0/50 - B25/50 - B25/50 - B25/51 - B25/52 - B25/50 - B25/50 - B25/51 - B25/52 - B25/50 - B25/51 - B25/52 - B25/55 - B25/100 - Operating Temperature - Operating Temperature - Power - Max - Length - Lead Wire 1.50° (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.0mm W		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C150kResistance Tolerance±10%B Value Tolerance-B Value Tolerance-B0/50-B25/50-B25/55-B25/554561KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeDisc, 2.8mm Dia x 3.0mm W	Package	Disc, 2.8mm Dia x 3.0mm W
Resistance Tolerance±10%B Value Tolerance-B0/50-B0/50-B25/50-B25/51-B25/52-B25/50-B25/50-B25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50° (38.00 mm)Mounting TypeDisc 2.8mn Dia x 3.0mm WPower CaseDisc 2.8mn Dia x 3.0mm W	Series	RL1004
B Value Tolerance-B Value Tolerance-B0/50-B 25/50-B 25/75-B 25/854561KB 25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Resistance in Ohms @ 25°C	150k
B0/50-B25/50-B25/75-B25/854561KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Resistance Tolerance	$\pm 10\%$
B25/50-B25/75-B25/854561KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B Value Tolerance	-
B25/75-B25/854561KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B0/50	-
B25/85 4561K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.0mm W	B25/50	-
B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.0mm W	B25/75	-
Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B25/85	4561K
Power - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	B25/100	-
Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Operating Temperature	-50°C ~ 150°C
Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.0mm W	Power - Max	-
Package / CaseDisc, 2.8mm Dia x 3.0mm W	Length - Lead Wire	1.50" (38.00mm)
	Mounting Type	Through Hole
	Package / Case	Disc, 2.8mm Dia x 3.0mm W
Report errors?		Report errors?

RL1004-81.1K-138-D1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

RL1004-81.1K-138-D1 Payment Methods



RL1004-81.1K-138-D1 Shipping Methods



If you have any question about RL1004-81.1K-138-D1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com