

RL1007-183K-155-D1

RL1007-183K-155-D1 Information

www.tpeisener.com	 RL1007-183K-155-D1 Amphenol Advanced Sensors Sensors, Transducers Temperature Sensors - NTC Thermistors NTC THERMISTOR 350K OHM 10% DISC Disc, 2.8mm Dia x 3.8mm W For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL1007-183K-155-D1 Specifications

Manufacturer Part Number RL1007-183K-155-D1 Manufacturer Amphenol Advanced Sensors Category Sensors, Transducers Temperature Sensors - NTC Thermistors Temperature Sensors - NTC Thermistors Package Disc, 2.8mm Dia x 3.8mm W Series RL1007 Resistance in Ohms @ 25°C 350k Resistance Tolerance ±10% B Value Tolerance - B/50 - B25/50 - B25/50 - B25/50 - B25/100 - Operating Temperature - Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.8mm W		
CategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 2.8mn Dia x 3.8mm WSeriesRL1007Resistance in Ohms @ 25°C350kResistance Tolerance+10%B Value Tolerance-B0/50-B25/50-B25/50-B25/514793KB25/100-Operating Temperature-0°C ~ 150°CPower - Max-Length - Lead Wire1.50°(38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mn Dia x 3.8mm W	Manufacturer Part Number	RL1007-183K-155-D1
Temperature Sensors - NTC ThermistorsPackageDisc, 2.8mm Dia x 3.8mm WSeriesRL1007Resistance in Ohms @ 25°C350kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/50-B25/504793KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeDisc, 2.8mm Dia x 3.8mm W	Manufacturer	Amphenol Advanced Sensors
PackageDisc, 2.8mn Dia x 3.8mn WSeriesRL1007Resistance in Ohms @ 25°C350kResistance Tolerance±10%B Value Tolerance-B Value Tolerance-B0/50-B25/50-B25/75-B25/854793KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C a 150°CMounting TypeThough HolePackage / CaseDisc, 2.8mn Dia x 3.8mn W	Category	Sensors, Transducers
Series RL1007 Resistance in Ohms @ 25°C 350k Resistance Tolerance ±10% B Value Tolerance - B Value Tolerance - B0/50 - B25/50 - Doperating Temperature - Power - Max - Length - Lead Wire 1.50° (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Dia x 3.8mm W		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C350kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/554793KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeDisc, 2.8mm Dia x 3.8mm W	Package	Disc, 2.8mm Dia x 3.8mm W
Resistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/854793KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	Series	RL1007
B Value Tolerance-B Value Tolerance-B 0/50-B 25/50-B 25/754793KB 25/85-B 25/100-Operating Temperature-0°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeFhrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	Resistance in Ohms @ 25°C	350k
B0/50-B25/50-B25/75-B25/854793KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	Resistance Tolerance	$\pm 10\%$
B25/50-B25/75-B25/854793KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 2.8mn Diax 3.8mn W	B Value Tolerance	-
B25/75-B25/854793KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	B0/50	-
B25/85 4793K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 150° (38.00mm) Mounting Type Through Hole Package / Case Disc, 28mm Diax 3.8mm W	B25/50	-
B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 2.8mm Diax 3.8mm W	B25/75	-
Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	B25/85	4793K
Power - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	B25/100	-
Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	Operating Temperature	-50°C ~ 150°C
Mounting TypeThrough HolePackage / CaseDisc, 2.8mm Dia x 3.8mm W	Power - Max	-
Package / CaseDisc, 2.8mm Dia x 3.8mm W	Length - Lead Wire	1.50" (38.00mm)
-	Mounting Type	Through Hole
Report errors?	Package / Case	Disc, 2.8mm Dia x 3.8mm W
		Report errors?

RL1007-183K-155-D1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

RL1007-183K-155-D1 Payment Methods



RL1007-183K-155-D1 Shipping Methods



If you have any question about RL1007-183K-155-D1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com