

RL2007-32.8-59-D1

RL2007-32.8-59-D1 Information

www.peisener.com	 RL2007-32.8-59-D1 Amphenol Advanced Sensors Sensors, Transducers Temperature Sensors - NTC Thermistors NTC THERMISTOR 50 OHM 10% DISC Disc, 5.6mm Dia x 4.1mm W For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL2007-32.8-59-D1 Specifications

Manufacturer Part Number RL2007-32.8-59-D1 Manufacturer Amphenol Advanced Sensors Category Sensors, Transducers Temperature Sensors - NTC Thermistors Temperature Sensors - NTC Thermistors Package Disc, 5.6mm Dia x 4.1mm W Series RL2007 Resistance in Ohms @ 25°C 50 Resistance Tolerance ±10% B Value Tolerance - B/50 - B25/50 - B25/50 - B25/50 - B25/100 - Operating Temperature - Operating Temperature - Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 5.6mm Dia x 4.1mm W		
CategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 5.6mm Dia x 4.1mm WSeriesRL2007Resistance in Ohms @ 25°C50Resistance Tolerance±10%B Value Tolerance-B0/500B25/50-B25/50096KB25/100-Operating Temperature50°C ~ 150°CPower - Max-Length - Lead Wire1.50°(38.00mm)Munting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	Manufacturer Part Number	RL2007-32.8-59-D1
Temperature Sensors - NTC Thermistors Package Disc, 5.6mm Dia x 4.1mm W Series RL2007 Resistance in Ohms @ 25°C 50 Resistance Tolerance ±10% B Value Tolerance - BV3lue Tolerance - BV50 - B25/50 - B25/50 - B25/50 3096K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 5.6mm Dia x 4.1mm W	Manufacturer	Amphenol Advanced Sensors
PackageDisc, 5.6mm Dia x 4.1mm WSeriesRL2007Resistance in Ohms @ 25°C50Resistance Tolerance±10%B Value Tolerance-B Value Tolerance-B0/50-B25/50-B25/51096KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeDisc, 5.6mm Dia x 4.1mm WPackage / CaseDisc, 5.6mm Dia x 4.1mm W	Category	Sensors, Transducers
Series RL2007 Resistance in Ohms @ 25°C 50 Resistance Tolerance ±10% B Value Tolerance - B Value Tolerance - B0/50 - B25/50 - B25/50 - B25/51 - B25/52 3096K B25/100 - Operating Temperature - Power - Max - Length - Lead Wire 1.50° (38.00mm) Mounting Type Through Hole Package / Case Disc, 5.6mm Dia x 4.1mm W		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C50Resistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/553096KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeDisc, 5.6mm Dia x 4.1mm W	Package	Disc, 5.6mm Dia x 4.1mm W
Resistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/55-B25/553096KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeDisc, 56mm Dia x 4.1mm W	Series	RL2007
B Value Tolerance-B Value Tolerance-B Value Tolerance-B Value Tolerance-B 25/50-B 25/753096KB 25/100-O perating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeFhrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	Resistance in Ohms @ 25°C	50
B0/50-B25/50-B25/75-B25/853096KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50° (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	Resistance Tolerance	±10%
B25/50-B25/75-B25/853096KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50°C ~ 150°CMounting TypeThrough HolePackage / CaseDisc, 5.6mm Diax 4.1mm W	B Value Tolerance	-
B25/75-B25/853096KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	B0/50	-
B25/85 3096K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 5.6mm Dia x 4.1mm W	B25/50	-
B25/100 - Operating Temperature -50°C ~ 150°C Power - Max - Length - Lead Wire 1.50" (38.00mm) Mounting Type Through Hole Package / Case Disc, 5.6mm Diax 4.1mm W	B25/75	-
Operating Temperature-50°C ~ 150°CPower - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	B25/85	3096K
Power - Max-Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	B25/100	-
Length - Lead Wire1.50" (38.00mm)Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	Operating Temperature	-50°C ~ 150°C
Mounting TypeThrough HolePackage / CaseDisc, 5.6mm Dia x 4.1mm W	Power - Max	-
Package / CaseDisc, 5.6mm Dia x 4.1mm W	Length - Lead Wire	1.50" (38.00mm)
-	Mounting Type	Through Hole
Report errors?	Package / Case	Disc, 5.6mm Dia x 4.1mm W
		Report errors?

RL2007-32.8-59-D1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RL2007-32.8-59-D1 Payment Methods



RL2007-32.8-59-D1 Shipping Methods



If you have any question about RL2007-32.8-59-D1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com