

RL2008-2010-103-D1

RL2008-2010-103-D1 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL2008-2010-103-D1 Specifications

Manufacturer Part NumberRL2008-2010-103-D1ManufacturerAmphenol Advanced SensorsCategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 5.6mm Dia x 4.3mm WSeriesRL2008Resistance in Ohms @ 25°C3.5kResistance Tolerance±10%BValue Tolerance-B0/50-B25/50-B25/514073KB25/100-Operating Temperature-Power - Max-Length - Lead Wire1.50" (38.00mm)		
CategorySensors, TransducersTemperature Sensors - NTC ThermistorsPackageDisc, 5.6mm Dia x 4.3mm WSeriesRL2008Resistance in Ohms @ 25°C3.5kResistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/50-B25/554073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Manufacturer Part Number	RL2008-2010-103-D1
Temperature Sensors - NTC ThermistorsPackageDisc, 5.6mm Dia x 4.3mm WSeriesRL2008Resistance in Ohms @ 25°C3.5kResistance Tolerance±10%B Value Tolerance-B0/50-B0/50-B25/50-B25/754073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Manufacturer	Amphenol Advanced Sensors
PackageDisc, 5.6mm Dia x 4.3mm WSeriesRL2008Resistance in Ohms @ 25°C3.5kResistance Tolerance±10%B Value Tolerance-B/50-B0/50-B25/50-B25/754073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Category	Sensors, Transducers
Series RL2008 Resistance in Ohms @ 25°C 3.5k Resistance Tolerance ±10% B Value Tolerance - B/50 - B0/50 - B25/50 - B25/75 - B25/85 4073K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -		Temperature Sensors - NTC Thermistors
Resistance in Ohms @ 25°C3.5kResistance Tolerance±10%B Value Tolerance-B0/50-B0/50-B25/50-B25/75-B25/854073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Package	Disc, 5.6mm Dia x 4.3mm W
Resistance Tolerance±10%B Value Tolerance-B0/50-B25/50-B25/75-B25/854073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Series	RL2008
B Value Tolerance-B0/50-B25/50-B25/75-B25/854073KB25/100-Operating Temperature-50°C ~ 150°CPower - Max-	Resistance in Ohms @ 25°C	3.5k
B0/50 - B25/50 - B25/75 - B25/85 4073K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -	Resistance Tolerance	±10%
B25/50 - B25/75 - B25/85 4073K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -	B Value Tolerance	-
B25/75 - B25/85 4073K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -	B0/50	-
B25/85 4073K B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -	B25/50	-
B25/100 - Operating Temperature -50°C ~ 150°C Power - Max -	B25/75	-
Operating Temperature-50°C ~ 150°CPower - Max-	B25/85	4073K
Power - Max -	B25/100	-
	Operating Temperature	-50°C ~ 150°C
Length - Lead Wire 1.50" (38.00mm)	Power - Max	-
	Length - Lead Wire	1.50" (38.00mm)
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Disc, 5.6mm Dia x 4.3mm W	Package / Case	Disc, 5.6mm Dia x 4.3mm W
Report errors?		Report errors?

RL2008-2010-103-D1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RL2008-2010-103-D1 Payment Methods



RL2008-2010-103-D1 Shipping Methods



If you have any question about RL2008-2010-103-D1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com