



RL20S164GRE6 Information

Heisener.com

Part NumberRL20S164GRE6ManufacturerVishay DaleCategoryResistors

Through Hole Resistors

Description RES 160K OHM 1/2W 2% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL20S164GRE6 Specifications

Manufacturer Part NumberRL20S164GRE6ManufacturerVishay DaleCategoryResistorsThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/02, RL20Resistance160 kOhmsTolerance±2%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxial
Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/02, RL20 Resistance 160 kOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C
Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/02, RL20 Resistance 160 kOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C
Package Axial Series Military, MIL-PRF-22684/02, RL20 Resistance 160 kOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C
SeriesMilitary, MIL-PRF-22684/02, RL20Resistance 160 kOhms Tolerance $\pm 2\%$ Power (Watts) 0.5W , $1/2\text{W}$ CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient $\pm 200\text{ppm/°C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Resistance 160 kOhms Tolerance $\pm 2\%$ Power (Watts) 0.5W , $1/2\text{W}$ CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient $\pm 200\text{ppm/}^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Tolerance $\pm 2\%$ Power (Watts) $0.5W, 1/2W$ Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ± 200 ppm/°C Operating Temperature -65 °C ~ 175 °C
Power (Watts) $0.5W$, $1/2W$ Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ± 200 ppm/°C Operating Temperature -65 °C ~ 175 °C
CompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient $\pm 200 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Operating Temperature $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$
Package / Case Axial
Supplier Device Package Axial
Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm)
Height - Seated (Max)
Number of Terminations 2
Failure Rate -
Report errors?

RL20S164GRE6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL20S164GRE6 Payment Methods



















RL20S164GRE6 Shipping Methods













If you have any question about RL20S164GRE6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com