



RL20S222JBSL Information

Heisener.com

Part NumberRL20S222JBSLManufacturerVishay DaleCategoryResistors

Through Hole Resistors

Description RES 2.2K OHM 1/2W 5% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL20S222JBSL Specifications

Manufacturer Part NumberRL20S222JBSLManufacturerVishay DaleCategoryResistorsPackageAxialSeriesMilitary, MIL-PRF-22684/02, RL20Resistance2.2 kOhmsTolerance±5%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.145" Dia x 0.375" L (3.68mm x 9.53mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	•	
Category Resistors Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/02, RL20 Resistance 2.2 kOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Manufacturer Part Number	RL20S222JBSL
Through Hole Resistors Package Axial Series Military, MIL-PRF-22684/02, RL20 Resistance 2.2 kOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-22684/02, RL20Resistance2.2 kOhmsTolerance±5%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.145" Dia x 0.375" L (3.68mm x 9.53mm)Height - Seated (Max)-Number of Terminations2Failure Rate-	Category	Resistors
SeriesMilitary, MIL-PRF-22684/02, RL20Resistance2.2 kOhmsTolerance±5%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Military, Moisture Resistant, SafetyTemperature Coefficient±200ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.145" Dia x 0.375" L (3.68mm x 9.53mm)Height - Seated (Max)-Number of Terminations2Failure Rate-		Through Hole Resistors
Resistance 2.2 kOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Package	Axial
Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Series	Military, MIL-PRF-22684/02, RL20
Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	2.2 kOhms
Composition Metal Film Features Flame Retardant Coating, Military, Moisture Resistant, Safety Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Tolerance	±5%
Features Flame Retardant Coating, Military, Moisture Resistant, Safety ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	0.5W, 1/2W
Temperature Coefficient ±200ppm/°C Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Composition	Metal Film
Operating Temperature -65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Features	Flame Retardant Coating, Military, Moisture Resistant, Safety
Package / Case Axial Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Temperature Coefficient	±200ppm/°C
Supplier Device Package Axial Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Operating Temperature	-65°C ~ 175°C
Size / Dimension 0.145" Dia x 0.375" L (3.68mm x 9.53mm) Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Package / Case	Axial
Height - Seated (Max) - Number of Terminations 2 Failure Rate -	Supplier Device Package	Axial
Number of Terminations 2 Failure Rate -	Size / Dimension	0.145" Dia x 0.375" L (3.68mm x 9.53mm)
Failure Rate -	Height - Seated (Max)	-
	Number of Terminations	2
	Failure Rate	-
Report errors?		Report errors?

RL20S222JBSL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL20S222JBSL Payment Methods



















RL20S222JBSL Shipping Methods













If you have any question about RL20S222JBSL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com