

RL2512JK-070R039L

RL2512JK-070R039L Information



Part Number	RL2512JK-070R039L	
Manufacturer	Yageo	
Category	Resistors Chip Resistor - Surface Mount	
Description	RES SMD 0.039 OHM 5% 1W 2512	
Package	2512 (6432 Metric)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RL2512JK-070R039L Specifications

Manufacturer Part NumberRL2512JK-070R039LManufacturerYageoCategoryResistorsChip Resistor - Surface MountPackage2512 (6432 Metric)SeriesRLResistance39 mOhmsTolerance±5%Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.00"		
CategoryResistorsCategoryChip Resistor - Surface MountPackage2512 (6432 Metric)PackageSpl2 (6432 Metric)SeriesRLResistance39 mOhmsTolerance±5%Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200pm/°COperating Temperature55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Manufacturer Part Number	RL2512JK-070R039L
Chip Resistor - Surface MountPackage2512 (6432 Metric)SeriesRLResistance39 mOhmsTolerance±5%Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature55° C ~ 155° CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250° L x 0.126° W (6.35mm x 3.20mm)Height - Seated (Max)0.026° (0.65mm)	Manufacturer	Yageo
Package2512 (6432 Metric)SeriesRLResistance39 mOhmsTolerance±5%Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Category	Resistors
SeriesRLResistance39 mOhmsTolerance±5%Power (Watts)1WCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200pm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)		Chip Resistor - Surface Mount
Resistance39 mOhmsTolerance±5%Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200pm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Package	2512 (6432 Metric)
Tolerance±5%Power (Watts)1WCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Series	RL
Power (Watts)IWCompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Resistance	39 mOhms
CompositionThick FilmFeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Tolerance	$\pm 5\%$
FeaturesAutomotive AEC-Q200, Current Sense, Moisture ResistantTemperature Coefficient±1200ppm/°COperating Temperature-55°C ~ 155°CPackage / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Power (Watts)	1W
Temperature Coefficient ±1200pm/°C Operating Temperature -55°C ~ 155°C Package / Case 2512 (6432 Metric) Supplier Device Package 2512 Size / Dimension 0.250" L x 0.126" W (6.35mm x 3.20mm) Height - Seated (Max) 0.026" (0.65mm)	Composition	Thick Film
Operating Temperature -55°C ~ 155°C Package / Case 2512 (6432 Metric) Supplier Device Package 2512 Size / Dimension 0.250" L x 0.126" W (6.35mm x 3.20mm) Height - Seated (Max) 0.026" (0.65mm)	Features	Automotive AEC-Q200, Current Sense, Moisture Resistant
Package / Case2512 (6432 Metric)Supplier Device Package2512Size / Dimension0.250" L x 0.126" W (6.35mm x 3.20mm)Height - Seated (Max)0.026" (0.65mm)	Temperature Coefficient	±1200ppm/°C
Supplier Device Package 2512 Size / Dimension 0.250" L x 0.126" W (6.35mm x 3.20mm) Height - Seated (Max) 0.026" (0.65mm)	Operating Temperature	-55°C ~ 155°C
Size / Dimension 0.250" L x 0.126" W (6.35mm x 3.20mm) Height - Seated (Max) 0.026" (0.65mm)	Package / Case	2512 (6432 Metric)
Height - Seated (Max) 0.026" (0.65mm)	Supplier Device Package	2512
	Size / Dimension	0.250" L x 0.126" W (6.35mm x 3.20mm)
	Height - Seated (Max)	0.026" (0.65mm)
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

RL2512JK-070R039L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

RL2512JK-070R039L Payment Methods



RL2512JK-070R039L Shipping Methods



If you have any question about RL2512JK-070R039L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com