



RL3720S-R47-G Information



For Reference Only

Part Number RL3720S-R47-G

Manufacturer Susumu
Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 0.47 OHM 1/2W 1508 WIDE

Package Wide 1508 (3720 Metric), 0815

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RL3720S-R47-G Specifications

Manufacturer Part Number RL3720S-R47-G Manufacturer Susumu Category Resistors Chip Resistor - Surface Mount Package Wide 1508 (3720 Metric), 0815 Series RL Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	•	
Category Resistors Chip Resistor - Surface Mount Package Wide 1508 (3720 Metric), 0815 Series RL Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/+200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer Part Number	RL3720S-R47-G
Chip Resistor - Surface Mount Package Wide 1508 (3720 Metric), 0815 Series RL Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/+200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Manufacturer	Susumu
Package Wide 1508 (3720 Metric), 0815 Series RL Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Category	Resistors
Series RL Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -		Chip Resistor - Surface Mount
Resistance 470 mOhms Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package	Wide 1508 (3720 Metric), 0815
Tolerance ±2% Power (Watts) 0.5W, 1/2W Composition Thin Film Features Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Series	RL
Power (Watts) Composition Thin Film Features Current Sense Temperature Coefficient O/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package O815 Size / Dimension O.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Resistance	470 mOhms
Composition Thin Film Current Sense Current Sense O/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Tolerance	±2%
Features Current Sense Current Sense Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) Number of Terminations 2 Failure Rate -	Power (Watts)	0.5W, 1/2W
Temperature Coefficient 0/ +200ppm/°C Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Composition	Thin Film
Operating Temperature -55°C ~ 125°C Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Features	Current Sense
Package / Case Wide 1508 (3720 Metric), 0815 Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Temperature Coefficient	0/ +200ppm/°C
Supplier Device Package 0815 Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.079" L x 0.148" W (2.00mm x 3.75mm) Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Package / Case	Wide 1508 (3720 Metric), 0815
Height - Seated (Max) 0.028" (0.70mm) Number of Terminations 2 Failure Rate -	Supplier Device Package	0815
Number of Terminations 2 Failure Rate -	Size / Dimension	0.079" L x 0.148" W (2.00mm x 3.75mm)
Failure Rate -	Height - Seated (Max)	0.028" (0.70mm)
	Number of Terminations	2
Report errors?	Failure Rate	-
		Report errors?

RL3720S-R47-G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RL3720S-R47-G Payment Methods



















RL3720S-R47-G Shipping Methods













If you have any question about RL3720S-R47-G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com