



### **RM 11AV Information**

Heisener.com

Part Number RM 11AV

Manufacturer Sanken

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

**Description** DIODE GEN PURP 600V 1.2A AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RM 11AV Specifications**

Manufacturer       RM 11 AV         Manufacturer       Sanken         Category       Discrete Semiconductor Products         Diodes - Rectifiers - Single         Package       Axial         Series       -         Diode Type       Standard         Voltage - DC Reverse (Vr) (Max)       600V         Current - Average Rectified (Io)       1.2A         Voltage - Forward (Vf) (Max) @ If       920mV @ 1.5A         Speed       Standard Recovery >500ns, > 200mA (Io)         Reverse Recovery Time (trr)       -         Current - Reverse Leakage @ Vr       10μA @ 600V         Capacitance @ Vr, F       -         Mounting Type       Through Hole         Package / Case       Axial         Supplier Device Package       Axial         Operating Temperature - Junction       -40°C ~ 150°C		
Category  Discrete Semiconductor Products  Diodes - Rectifiers - Single  Axial  Series  - Diode Type  Standard  Voltage - DC Reverse (Vr) (Max)  Current - Average Rectified (Io)  1.2A  Voltage - Forward (Vf) (Max) @ If  Speed  Standard Recovery >500ns, > 200mA (Io)  Reverse Recovery Time (trr)  - Current - Reverse Leakage @ Vr  10µA @ 600V  Capacitance @ Vr, F  Mounting Type  Through Hole  Package / Case  Axial  Operating Temperature - Junction  Javial  Axial  Descriptions  Discrete Semiconductor Products  Diodes - Rectifiers - Single  Axial	Manufacturer Part Number	RM 11AV
PackageDiodes - Rectifiers - SinglePackageAxialSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)1.2AVoltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Manufacturer	Sanken
PackageAxialSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)1.2AVoltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)1.2AVoltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)1.2AVoltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Package	Axial
Voltage - DC Reverse (Vr) (Max)  Current - Average Rectified (Io)  1.2A  Voltage - Forward (Vf) (Max) @ If  Speed  Standard Recovery >500ns, > 200mA (Io)  Reverse Recovery Time (trr)  -  Current - Reverse Leakage @ Vr  10μA @ 600V  Capacitance @ Vr, F  Mounting Type  Through Hole  Package / Case  Axial  Supplier Device Package  Operating Temperature - Junction  600V  1.2A  920mV @ 1.5A  920	Series	-
Current - Average Rectified (Io)1.2AVoltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If920mV @ 1.5ASpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	600V
SpeedStandard Recovery >500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Current - Average Rectified (Io)	1.2A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr10μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseAxialSupplier Device PackageAxialOperating Temperature - Junction-40°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	920mV @ 1.5A
Current - Reverse Leakage @ Vr	Speed	Standard Recovery >500ns, > 200mA (Io)
Capacitance @ Vr, F  Mounting Type  Through Hole  Package / Case  Axial  Supplier Device Package  Axial  Operating Temperature - Junction  -40°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting Type Through Hole Package / Case Axial Supplier Device Package Axial Operating Temperature - Junction  Through Hole Axial  -40°C ~ 150°C	Current - Reverse Leakage @ Vr	10μA @ 600V
Package / Case Axial  Supplier Device Package Axial  Operating Temperature - Junction -40°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device Package Axial  Operating Temperature - Junction $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Mounting Type	Through Hole
Operating Temperature - Junction $-40^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Package / Case	Axial
	Supplier Device Package	Axial
Report errors?	Operating Temperature - Junction	-40°C ~ 150°C
1		Report errors?

#### **RM 11AV Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RM 11AV Payment Methods**



















# **RM 11AV Shipping Methods**













If you have any question about RM 11AV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com