



Heisener.com

RM15WTRZA-3S(72) Information

Part NumberRM15WTRZA-3S(72)ManufacturerHirose Electric Co LtdCategoryConnectors, Interconnects
Circular Connectors

Description CONN RCPT 3POS JAM NUT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RM15WTRZA-3S(72) Specifications

| Manufacturer Part Number RM15WTRZA-3S(72) Manufacturer Hirose Electric Co Ltd Category Connectors, Interconnects Package - Series RM-W Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 15 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | | |
|--|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesRM-WConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | Manufacturer Part Number | RM15WTRZA-3S(72) |
| Package-SeriesRM-WConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | Manufacturer | Hirose Electric Co Ltd |
| Package-SeriesRM-WConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | Category | Connectors, Interconnects |
| SeriesRM-WConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | | Circular Connectors |
| Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 15 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Package | - |
| Number of Positions3Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | Series | RM-W |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 15 | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Number of Positions | 3 |
| Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating10A | Shell Size - Insert | 15 |
| Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Shell Size, MIL | - |
| Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Mounting Type | Panel Mount, Bulkhead - Front Side Nut |
| Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Termination | Solder Cup |
| Ingress Protection IP67 - Dust Tight, Waterproof Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Gold - VOLTAGE - VOLTAGE 10A | Orientation | Keyed |
| Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Ingress Protection | IP67 - Dust Tight, Waterproof |
| Features - Voltage - Rated 500VAC, 700VDC Current Rating 10A | Shell Material, Finish | Zinc, Brass, Pliable PVC, Chrome or Nickel Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating 10A | Contact Finish | Gold |
| Current Rating 10A | Features | - |
| č | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | 10A |
| | | Report errors? |

RM15WTRZA-3S(72) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RM15WTRZA-3S(72) Payment Methods



















RM15WTRZA-3S(72) Shipping Methods













If you have any question about RM15WTRZA-3S(72), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com