



### RM15WTRZB-2P(71) Information



For Reference Only

Part Number RM15WTRZB-2P(71)

Manufacturer Hirose Electric Co Ltd

Category Connectors, Interconnects
Circular Connectors

**Description** CONN RCPT 2POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# RM15WTRZB-2P(71) Specifications

Manufacturer Part NumberRM15WTRZB-2P(71)ManufacturerHirose Electric Co LtdCategoryConnectors, InterconnectsPackage-SeriesRM-WConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A		
CategoryConnectors, InterconnectsPackage-SeriesRM-WConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Manufacturer Part Number	RM15WTRZB-2P(71)
Package-SeriesRM-WConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Manufacturer	Hirose Electric Co Ltd
Package-SeriesRM-WConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Category	Connectors, Interconnects
SeriesRM-WConnector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Package	-
Number of Positions2Shell Size - Insert15Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Series	RM-W
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Silver Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded  Orientation Keyed  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 600VAC, 840VDC  Current Rating 10A	Number of Positions	2
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishZinc, Brass, Pliable PVC, Chrome or Nickel PlatedContact FinishSilverFeatures-Voltage - Rated600VAC, 840VDCCurrent Rating10A	Shell Size - Insert	15
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Silver Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Shell Size, MIL	-
Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Silver Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Mounting Type	Panel Mount, Flange
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Silver Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Zinc, Brass, Pliable PVC, Chrome or Nickel Plated Contact Finish Silver Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Zinc, Brass, Pliable PVC, Chrome or Nickel Plated  Silver  - Under Plated  600VAC, 840VDC  10A	Orientation	Keyed
Contact Finish Silver  Features - Voltage - Rated 600VAC, 840VDC  Current Rating 10A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 600VAC, 840VDC Current Rating 10A	Shell Material, Finish	Zinc, Brass, Pliable PVC, Chrome or Nickel Plated
Voltage - Rated 600VAC, 840VDC Current Rating 10A	Contact Finish	Silver
Current Rating 10A	Features	-
- Company of the Comp	Voltage - Rated	600VAC, 840VDC
Report errors?	Current Rating	10A
		Report errors?

### RM15WTRZB-2P(71) Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## RM15WTRZB-2P(71) Payment Methods



















## RM15WTRZB-2P(71) Shipping Methods













If you have any question about RM15WTRZB-2P(71), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com