

RM205524 Information

nelse m

For Reference Only

Part Number RM205524

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 16A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RM205524 Specifications

Manufacturer Part NumberRM205524ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact FormDPDT (2 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VAC
Category Relays Power Relays, Over 2 Amps Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Coil Type Non Latching Coil Current Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Coil Current - Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Coil Voltage 24VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Contact Form DPDT (2 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Contact Rating (Current) Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Switching Voltage 440VAC - Max Turn On Voltage (Max) 19.2 VAC
Turn On Voltage (Max) 19.2 VAC
Turn Off Voltage (Min) 7.2 VAC
Operate Time -
Release Time -
Features Mechanical Indicator
Mounting Type Chassis Mount
Termination Style Quick Connect - 0.250" (6.3mm)
Report errors

RM205524 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RM205524 Payment Methods





















RM205524 Shipping Methods













If you have any question about RM205524, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com