

### RM702730 Information

theisener.con

For Reference Only

Part Number RM702730

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 16A 230V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RM702730 Specifications**

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Relays  Power Relays, Over 2 Amps  Package  - Series  RM, SCHRACK  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  - Coil Voltage  230VAC  Contact Form  3PDT (3 Form C)  Contact Rating (Current)  16A  Switching Voltage  440VAC - Max  Turn On Voltage (Max)  184 VAC  Operate Time  - Release Time  -  Te Connectivity Potter & Brumfield Relays  Relays  Te Connectivity Potter & Brumfield Relays  Power Relays  Power Relays  Power Relays  Andro  Power Relays  Andro  Power Relays  Amps  Power Relays  Andro  Power Relays  Power Amps  -  Te Connectivity Potter & Brumfield Relays  Power Andro  Power Relays  Andro  Power Relays  Power Relays  Power Relays  Power Andro  Power Relays  Power Andro  Power Relays  Andro  Power Relays  Power Andro  Power Amps  Andro  Power Relays  Power Andro  Powe		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         RM, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         -           Coil Voltage         230VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         16A           Switching Voltage         440VAC - Max           Turn On Voltage (Max)         184 VAC           Turn Off Voltage (Min)         69 VAC           Operate Time         -	Manufacturer Part Number	RM702730
Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Operate Time	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time	Category	Relays
Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time -		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current - Coil Voltage 230VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 16A  Switching Voltage 440VAC - Max  Turn On Voltage (Max) 184 VAC  Turn Off Voltage (Min) 69 VAC  Operate Time -	Package	-
Coil Type Non Latching  Coil Current - Coil Voltage 230VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 16A  Switching Voltage 440VAC - Max  Turn On Voltage (Max) 184 VAC  Turn Off Voltage (Min) 69 VAC  Operate Time -	Series	RM, SCHRACK
Coil Current         -           Coil Voltage         230VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         16A           Switching Voltage         440VAC - Max           Turn On Voltage (Max)         184 VAC           Turn Off Voltage (Min)         69 VAC           Operate Time         -	Relay Type	General Purpose
Coil Voltage 230VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 16A  Switching Voltage 440VAC - Max  Turn On Voltage (Max) 184 VAC  Turn Off Voltage (Min) 69 VAC  Operate Time -	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 16A  Switching Voltage 440VAC - Max  Turn On Voltage (Max) 184 VAC  Turn Off Voltage (Min) 69 VAC  Operate Time -	Coil Current	-
Contact Rating (Current)  Switching Voltage  440VAC - Max  Turn On Voltage (Max)  184 VAC  Turn Off Voltage (Min)  69 VAC  Operate Time  -	Coil Voltage	230VAC
Switching Voltage 440VAC - Max  Turn On Voltage (Max) 184 VAC  Turn Off Voltage (Min) 69 VAC  Operate Time -	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  184 VAC  Turn Off Voltage (Min)  69 VAC  Operate Time  -	Contact Rating (Current)	16A
Turn Off Voltage (Min) 69 VAC Operate Time -	Switching Voltage	440VAC - Max
Operate Time -	Turn On Voltage (Max)	184 VAC
	Turn Off Voltage (Min)	69 VAC
Release Time	Operate Time	-
Transport Time	Release Time	-
Features Mechanical Indicator	Features	Mechanical Indicator
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
Report errors?		Report errors?

### RM702730 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RM702730 Payment Methods**



















### **RM702730 Shipping Methods**













If you have any question about RM702730, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com