



RM732LC4 Information



For Reference Only

Part Number RM732LC4

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 16A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RM732LC4 Specifications

Manufacturer Part Number RM732LC4 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 70.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current70.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	RM732LC4
Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 70.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current70.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current70.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current70.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Package	-
Coil Type Non Latching Coil Current 70.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Series	RM, SCHRACK
Coil Current70.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Current	70.8mA
Contact Rating (Current) Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Voltage	24VDC
Switching Voltage 440VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) 2.4 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Switching Voltage	440VAC - Max
Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	2.4 VDC
Features Diode, LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Release Time	10ms
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Features	Diode, LED Indicator, Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
		Report errors?

RM732LC4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RM732LC4 Payment Methods





















RM732LC4 Shipping Methods













If you have any question about RM732LC4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com