

RM732T30 Information



For Reference Only

Part Number RM732T30

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 16A 230V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RM732T30 Specifications

Manufacturer Part Number RM732T30 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time-Release Time-FeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	RM732T30
Package-SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time-Release Time-FeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - RM, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesRM, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact Form3PDT (3 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)69 VACOperate Time-Release Time-FeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Series	RM, SCHRACK
Coil Current Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time	Relay Type	General Purpose
Coil Voltage 230VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Current	-
Contact Rating (Current) Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Voltage	230VAC
Switching Voltage 440VAC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 69 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Switching Voltage	440VAC - Max
Operate Time - Release Time - LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	184 VAC
Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	69 VAC
Features LED Indicator, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Operate Time	-
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Release Time	-
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Features	LED Indicator, Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
		Report errors?

RM732T30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RM732T30 Payment Methods



















RM732T30 Shipping Methods













If you have any question about RM732T30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com