

RMA15DTAH

RMA15DTAH Information

Heisener.com	 RMA15DTAH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 30POS 0.125 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RMA15DTAH Specifications

Manufacturer Part NumberRMA15DTAHManufacturerSulins Connector SolutionsCategoryConnectors InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions/Bay/Rom006? (1.57mm)Yinther of Rows0.125° (3.18mm)Yinther of Rows1.125° (3.18mm)Features-Mounting TypeSolderContact FinishSolderContact FinishSolderContact FinishGoldContact Finish ThicknessSolidon SongColorGreenFinage FeatureSolidon SongColorGreenFinage FeatureSolidon SongColorGreenFinage FeatureSolor ColorsSolor Col		
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Card Thickness0062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type5Contact MaterialSolderContact FinishGoldContact FinishGoldContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeGongellowsFage FeatureGreenFinish FinishGreenFinish FinishGreenContact SectionFinish Contact SectionContact FinishGreenFinish FinishGreenFinish FinishFinish Contact SectionContact FinishGreenFinish FinishFinish Contact SectionContact Finish FinishFinish Contact SectionContact Finish FinishGreenFinish FinishFinish Contact SectionContact Finish FinishFinish Contact Section	Manufacturer Part Number	RMA15DTAH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type5Contact MaterialSolderContact Finish Thickness6oldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColoarGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact Finish ThicknessGoldContact TypeGoldContact TypeGonge BlowsColorGreenFauresTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSup BellowsContact TypeGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeNon Specified AngleTornat AtteriationSolderContact FinishGoldContact FinishGoldContact TypeJojin (0.76µm)Contact TypeGolgellowsColorGreenFange FeaturesTor Mount Opening, Unthreaded, 0.125" (3.18mm) Dial	Package	-
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type1fnough Hole, Right AngleTerminationSolderContact MaterialPolsphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions30Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColorGreenFlange FeaturesTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeaturesTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	15
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	30
Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opting, Unit Provide, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount On Loop Solder	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.125" (3.18mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze
Contact TypeLoop BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows
	Color	Green
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
	Operating Temperature	-65°C ~ 125°C
Report errors?		Report errors?

RMA15DTAH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RMA15DTAH Payment Methods



RMA15DTAH Shipping Methods



If you have any question about RMA15DTAH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com