



RMM43DRES Information

Heisener.com

Part Number RMM43DRES

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 86POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RMM43DRES Specifications

Manufacturer Part Number RMM43DRES Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Contact Material Phosphor Bronze Contact Hinish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Kiviivi+3DKLS Specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	RMM43DRES	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
Gender Female Number of Positions/Bay/Row 43 Number of Positions 86 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row43Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions86Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	43	
Number of Rows2Pitch $0.156"$ (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 30μ in (0.76 μ m)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65° C ~ 125°C	Number of Positions	86	
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 30μ in $(0.76\mu$ m)Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 125 °C	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeFull BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature -65 °C ~ 125 °C	Termination	Solder Eyelet(s)	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze	
Contact Type Full Bellows Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color Green Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ∼ 125°C	
		Report	errors?

RMM43DRES Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RMM43DRES Payment Methods



















RMM43DRES Shipping Methods













If you have any question about RMM43DRES, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com