

RNR55H1102DSBSL

RNR55H1102DSBSL Information

En la 1949
3627
그의 연물
E1461/9
Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

RNR55H1102DSBSL Specifications

Manufacturer Part Number RNR55H1102DSBSL Manufacturer Vishay Dale Category Resistors Package Axial Package Miltary, MIL-PRF-55182/01, RNR55 Resistance 11 kOhms Tolerance ±0.5% Power (Watts) 0.125W, 1/8W Composition Metal Film Features Military, Moisture Resistant Operating Temperature 65°C ~ 175°C Package / Case Axial Supplier Device Package Axial Stape / Case Axial Number of Terminations 2 Failure Rate S(0.001%)		
CategoryResistorsThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-PRF-55182/01, RNR55Resistance11 kOhmsTolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50ppm°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)2Number of Terminations2Failure Rate\$(0.001%)	Manufacturer Part Number	RNR55H1102DSBSL
PackageThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-PRF-55182/01, RNR55Resistance11 kOhmsTolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure Rate\$(0.001%)	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-55182/01, RNR55Resistance11 kOhmsTolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)2Failure Rate\$ (0.001%)	Category	Resistors
SeriesMilitary, MIL-PRF-55182/01, RNR55Series11 kOhmsResistance11 kOhmsTolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50pm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)2Number of Terminations2Failure Rate\$(0.01%)		Through Hole Resistors
Resistance11 kOhmsTolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure Rate\$(0.001%)	Package	Axial
Tolerance±0.5%Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50pm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS(0.001%)	Series	Military, MIL-PRF-55182/01, RNR55
Power (Watts)0.125W, 1/8WCompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50pm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device Package0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure Rate\$ (0.001%)	Resistance	11 kOhms
CompositionMetal FilmFeaturesMilitary, Moisture ResistantTemperature Coefficient±50pm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS(0.001%)	Tolerance	$\pm 0.5\%$
FeaturesMilitary, Moisture ResistantTemperature Coefficient±50ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS(0.001%)	Power (Watts)	0.125W, 1/8W
Temperature Coefficient±50ppm/°COperating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS(0.001%)	Composition	Metal Film
Operating Temperature-65°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS (0.001%)	Features	Military, Moisture Resistant
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS (0.001%)	Temperature Coefficient	±50ppm/°C
Supplier Device PackageAxialSize / Dimension0.094" Dia x 0.250" L (2.39mm x 6.35mm)Height - Seated (Max)-Number of Terminations2Failure RateS (0.001%)	Operating Temperature	-65°C ~ 175°C
Number of Terminations0.094" Dia x 0.250" L (2.39mm x 6.35mm)Failure Rate0.094" Dia x 0.250" L (2.39mm x 6.35mm)S (0.001%)0.094" Dia x 0.250" L (2.39mm x 6.35mm)	Package / Case	Axial
Height - Seated (Max)-Number of Terminations2Failure RateS (0.001%)	Supplier Device Package	Axial
Number of Terminations2Failure RateS (0.001%)	Size / Dimension	0.094" Dia x 0.250" L (2.39mm x 6.35mm)
Failure RateS (0.001%)	Height - Seated (Max)	-
	Number of Terminations	2
Report errors?	Failure Rate	S (0.001%)
		Report errors?

RNR55H1102DSBSL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RNR55H1102DSBSL Payment Methods



If you have any question about RNR55H1102DSBSL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com