

### **RP1-1.5V Information**



For Reference Only

Part Number RP1-1.5V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY RF SPDT 100MA 1.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RP1-1.5V Specifications**

Manufacturer Part NumberRP1-1.5VManufacturerPanasonic Electric WorksCategoryRelaysBackage-SeriesRPRelay TypeRFCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)100mASwitching Voltage30VDC - NomTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesRPRelay TypeRFCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5 VDCContact FormSPDT (1 Form C)Contact Rating (Current)100mASwitching Voltage30 VDC - NomTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RP1-1.5V
Package-SeriesRPRelay TypeRFCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)100mASwitching Voltage30VDC - NomTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series RP Relay Type RF Coil Type Non Latching Coil Current 93.8mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 100mA Switching Voltage 30VDC - Nom Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRPRelay TypeRFCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)100mASwitching Voltage30VDC - NomTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 93.8mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 100mA Switching Voltage 30VDC - Nom Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)100mASwitching Voltage30VDC - NomTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	RP
Coil Current 93.8mA  Coil Voltage 1.5VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 100mA  Switching Voltage 30VDC - Nom  Turn On Voltage (Max) 1.13 VDC  Turn Off Voltage (Min) 0.15 VDC  Operate Time 3ms  Release Time 2ms  Features	Relay Type	RF
Coil Voltage 1.5VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 100mA  Switching Voltage 30VDC - Nom  Turn On Voltage (Max) 1.13 VDC  Turn Off Voltage (Min) 0.15 VDC  Operate Time 3ms  Release Time 2ms  Features	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  30VDC - Nom  Turn On Voltage (Max)  1.13 VDC  Turn Off Voltage (Min)  Operate Time  Release Time  Peatures  Mounting Type  Through Hole  Termination Style  SPDT (1 Form C)  100mA  30VDC - Nom  1.13 VDC  0.15 VDC	Coil Current	93.8mA
Contact Rating (Current)  Switching Voltage  30VDC - Nom  Turn On Voltage (Max)  1.13 VDC  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  2ms  Features  -  Mounting Type  Through Hole  Termination Style	Coil Voltage	1.5VDC
Switching Voltage 30VDC - Nom Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  1.13 VDC  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  2ms  Features  - Mounting Type  Through Hole  Termination Style  1.13 VDC  0.15 VDC  3ms  7ms  PC Pin	Contact Rating (Current)	100mA
Turn Off Voltage (Min)  Operate Time  3ms  Release Time  2ms  Features  -  Mounting Type  Through Hole  Termination Style  O.15 VDC  3ms  Through Hole  PC Pin	Switching Voltage	30VDC - Nom
Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	1.13 VDC
Release Time 2ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.15 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	2ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **RP1-1.5V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RP1-1.5V Payment Methods**



















### **RP1-1.5V Shipping Methods**













If you have any question about RP1-1.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com