

## RR02J3R0TB

#### **RR02J3R0TB** Information

Heisener.com	 RR02J3R0TB TE Connectivity Passive Product Resistors Through Hole Resistors RES 3.0 OHM 2W 5% AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RR02J3R0TB** Specifications

Manufacturer Part NumberRR02J3R0TBManufacturerTE Connectivity Passive ProductCategoryResistorsThrough Hole ResistorsThrough Hole ResistorsPackageAxialSeriesRR, NeohmResistance3 OhmsTolerance±5%Power (Watts)QWCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyPoreating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138° Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-		
CategoryResistorsThrough Hole ResistorsPackageAxialSeriesRR, NeohmResistance3 OhmsTolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyPoperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAialHeight - Seated (Max)-	Manufacturer Part Number	RR02J3R0TB
Hough Hole ResistorsPackageAxialSeriesRR, NeohmResistance3 OhmsTolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyOperating Temperature>55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialHingh L. Sated (Max)- 308°Dia x 0.354° L (3.50mm x 9.00mm)Height - Seated (Max)- 308°Dia x 0.354° L (3.50mm x 9.00mm)	Manufacturer	TE Connectivity Passive Product
PackageAxialSeriesRR, NeohmResistance3 OhmsTolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyOperating Temperature±300ppm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Category	Resistors
SeriesRR, NeohmResistance3 OhmsTolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-		Through Hole Resistors
Resistance3 OhmsTolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300pm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device Package0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Package	Axial
Tolerance±5%Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300pm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Series	RR, Neohm
Power (Watts)2WCompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300pm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Resistance	3 Ohms
CompositionMetal FilmFeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300pm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Tolerance	±5%
FeaturesFlame Retardant Coating, Pulse Withstanding, SafetyTemperature Coefficient±300ppm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Power (Watts)	2W
Temperature Coefficient±300pm/°COperating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Composition	Metal Film
Operating Temperature-55°C ~ 235°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Features	Flame Retardant Coating, Pulse Withstanding, Safety
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Temperature Coefficient	±300ppm/°C
Supplier Device PackageAxialSize / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Operating Temperature	-55°C ~ 235°C
Size / Dimension0.138" Dia x 0.354" L (3.50mm x 9.00mm)Height - Seated (Max)-	Package / Case	Axial
Height - Seated (Max) -	Supplier Device Package	Axial
	Size / Dimension	0.138" Dia x 0.354" L (3.50mm x 9.00mm)
	Height - Seated (Max)	-
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors		Report errors?

#### **RR02J3R0TB** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RR02J3R0TB** Payment Methods



### **RR02J3R0TB** Shipping Methods



If you have any question about RR02J3R0TB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com