



RR0816P-304-D Information



For Reference Only

Part Number RR0816P-304-D

Manufacturer Susumu
Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 300K OHM 0.5% 1/16W 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RR0816P-304-D Specifications

Manufacturer Part Number RR0816P-304-D Manufacturer Susumu Category Resistors Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series RR Resistance 300 kOhms Tolerance ±0.5% Power (Watts) 0.063W, 1/16W Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package - Size / Dimension 0.063" L. v. 0.031" W. (1.60mm v. 0.80mm)	*	
Category Resistors Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series RR Resistance 300 kOhms Tolerance ±0.5% Power (Watts) 0.063W, 1/16W Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -	Manufacturer Part Number	RR0816P-304-D
Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series RR Resistance 300 kOhms Tolerance ±0.5% Power (Watts) 0.063W, 1/16W Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -	Manufacturer	Susumu
Package 0603 (1608 Metric) Series RR Resistance 300 kOhms Tolerance ±0.5% Power (Watts) 0.063W, 1/16W Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -	Category	Resistors
Series RR Resistance 300 kOhms Tolerance ±0.5% Power (Watts) 0.063W, 1/16W Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -		Chip Resistor - Surface Mount
Resistance 300 kOhms Tolerance $\pm 0.5\%$ Power (Watts) 0.063W , $1/16\text{W}$ CompositionThin FilmFeatures-Temperature Coefficient $\pm 25\text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $0603 (1608 \text{ Metric})$ Supplier Device Package-	Package	0603 (1608 Metric)
Tolerance $\pm 0.5\%$ Power (Watts) $0.063W, 1/16W$ Composition Thin Film Features - Temperature Coefficient $\pm 25 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $0603 (1608 \text{ Metric})$ Supplier Device Package -	Series	RR
Power (Watts) $0.063W$, $1/16W$ CompositionThin FilmFeatures-Temperature Coefficient $\pm 25 ppm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Package / Case $0603 (1608 \text{ Metric})$ Supplier Device Package-	Resistance	300 kOhms
Composition Thin Film Features - Temperature Coefficient ±25ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -	Tolerance	±0.5%
Features - Temperature Coefficient $\pm 25 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $0603 (1608 \text{ Metric})$ Supplier Device Package -	Power (Watts)	0.063W, 1/16W
Temperature Coefficient $\pm 25 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $0603 (1608 \text{ Metric})$ Supplier Device Package $-$	Composition	Thin Film
Operating Temperature -55°C ~ 125°C Package / Case 0603 (1608 Metric) Supplier Device Package -	Features	-
Package / Case 0603 (1608 Metric) Supplier Device Package -	Temperature Coefficient	±25ppm/°C
Supplier Device Package -	Operating Temperature	-55°C ~ 125°C
	Package / Case	0603 (1608 Metric)
Size / Dimension 0.063" L v 0.031" W (1.60mm v 0.80mm)	Supplier Device Package	-
Size / Difficusion 0.003 L x 0.031 W (1.00min)	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)
Height - Seated (Max) 0.020" (0.50mm)	Height - Seated (Max)	0.020" (0.50mm)
Number of Terminations 2	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

RR0816P-304-D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RR0816P-304-D Payment Methods





















RR0816P-304-D Shipping Methods













If you have any question about RR0816P-304-D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com