

RRS325 Information

(A) Heisener.com

For Reference Only

Part Number RRS325 Manufacturer Ohmite

Category Potentiometers, Variable Resistors

Rotary Potentiometers, Rheostats

Description POT 325 OHM 500W WIREWOUND LIN

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RRS325 Specifications

Manufacturer Part Number RRS325 Manufacturer Ohmite Category Potentiometers, Variable Resistors Rotary Potentiometers, Rheostats Package - Series R Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length Actuator Diameter 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread Mounting Type Panel Mount	*	
Category Potentiometers, Variable Resistors Package - Scries R Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Manufacturer Part Number	RRS325
Package - Series R Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Manufacturer	Ohmite
Package - Series R Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Category	Potentiometers, Variable Resistors
Series R Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount		Rotary Potentiometers, Rheostats
Taper Linear Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Package	-
Resistance (Ohms) 325 Tolerance ±10% Number of Gangs 1 Built in Switch None Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Series	R
Tolerance±10%Number of Gangs1Built in SwitchNonePower (Watts)500WTemperature Coefficient-Number of Turns1Rotation325°Adjustment TypeUser DefinedResistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length2.000" (50.80mm)Actuator Diameter0.375" (9.53mm)Bushing Thread-Mounting TypePanel Mount	Taper	Linear
Number of Gangs1Built in SwitchNonePower (Watts)500WTemperature Coefficient-Number of Turns1Rotation325°Adjustment TypeUser DefinedResistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length2.000" (50.80mm)Actuator Diameter0.375" (9.53mm)Bushing Thread-Mounting TypePanel Mount	Resistance (Ohms)	325
Built in Switch Power (Watts) 500W Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Wirewound Termination Style Actuator Type Flatted Actuator Length Actuator Diameter Bushing Thread Mounting Type Panel Mount	Tolerance	±10%
Power (Watts) Temperature Coefficient - Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length Actuator Diameter Bushing Thread Mounting Type Panel Mount	Number of Gangs	1
Temperature Coefficient Number of Turns 1 Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length Actuator Diameter 0.375" (9.53mm) Bushing Thread Mounting Type Panel Mount	Built in Switch	None
Number of Turns Rotation 325° Adjustment Type User Defined Wirewound Termination Style Actuator Type Flatted Actuator Length Actuator Diameter Bushing Thread Mounting Type 1 1 1 1 1 1 1 1 1 1 1 1 1	Power (Watts)	500W
Rotation 325° Adjustment Type User Defined Resistive Material Wirewound Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Temperature Coefficient	-
Adjustment Type Resistive Material Wirewound Termination Style Actuator Type Flatted Actuator Length Actuator Diameter Bushing Thread Mounting Type User Defined Wirewound Virewound Virewound Solder Lug Solder Lug Flatted 2.000" (50.80mm) 0.375" (9.53mm) Panel Mount	Number of Turns	1
Resistive MaterialWirewoundTermination StyleSolder LugActuator TypeFlattedActuator Length2.000" (50.80mm)Actuator Diameter0.375" (9.53mm)Bushing Thread-Mounting TypePanel Mount	Rotation	325°
Termination Style Solder Lug Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Adjustment Type	User Defined
Actuator Type Flatted Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Resistive Material	Wirewound
Actuator Length 2.000" (50.80mm) Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Termination Style	Solder Lug
Actuator Diameter 0.375" (9.53mm) Bushing Thread - Mounting Type Panel Mount	Actuator Type	Flatted
Bushing Thread - Mounting Type Panel Mount	Actuator Length	2.000" (50.80mm)
Mounting Type Panel Mount	Actuator Diameter	0.375" (9.53mm)
	Bushing Thread	-
Report errors?	Mounting Type	Panel Mount
1		Report errors?

RRS325 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RRS325 Payment Methods





















RRS325 Shipping Methods













If you have any question about RRS325, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com