

RS1KL RHG

est a Quote

RS1KL RHG Information

Heisener.com Gittal Write Land Terr	Part Number	RS1KL RHG	
	Manufacturer	TSC America Inc.	
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	2
	Description	DIODE, FAST, 0.8A, 800V, 500NS,	5
	Package	DO-219AB	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RS1KL RHG Specifications

Manufacturer Part NumberRS1KL RHGManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SingleDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VSupplier Device Package500-219ABSupplier Device Package5ub SMAOperating Temperature - Junction-5b°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µJa @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-5°C ~ 150°C	Manufacturer Part Number	RS1KL RHG
Nodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Jo) 800 mAVoltage - Forward (Vf) (Max) @ If $1.3V @ 800$ mASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr) 500 nsCurrent - Reverse Leakage @ Vr $5\muA @ 800V$ Current - Reverse Leakage @ Vr $5\muF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $-5°C ~ 150°C$	Manufacturer	TSC America Inc.
PackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Jo)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series - Series - Diode Type Standard Voltage - DC Reverse (Vr) (Max) 800V Current - Average Rectified (Jo) 800mA Voltage - Forward (Vf) (Max) @ If 1.3V @ 800mA Speed Fast Recovery = < 500ms, > 200mA (Jo) Reverse Recovery Time (trr) 50ns Current - Reverse Leakage @ Vr 500ns Current - Reverse Leakage @ Vr 50P @ 4V, 1MHz Mounting Type Surface Mount Package / Case Do-219AB Supplier Device Package Sub SMA Operating Temperature - Junction 50°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C	Package	DO-219AB
Yoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Jo) $800mA$ Voltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5µA @ 800V$ Capacitance @ Vr, F $10pF @ 4V$, 1MHzMounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction $-55°C \sim 150°C$	Series	-
Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr $5µA @ 800V$ Capacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5\mu A @ 800V$ Capacitance @ Vr, F $10pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150° C	Voltage - DC Reverse (Vr) (Max)	800V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	800mA
Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5μA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 800mA
Current - Reverse Leakage @ Vr5μA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	500ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 800V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	10pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors'	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

RS1KL RHG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RS1KL RHG Payment Methods



RS1KL RHG Shipping Methods



If you have any question about RS1KL RHG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com