

RS1KLHM2G

RS1KLHM2G Information

Heisener.com	 RS1KLHM2G TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, FAST, 0.8A, 800V, 500NS, DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RS1KLHM2G Specifications

Manufacturer Part NumberR\$1KLHM2GManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SingleDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mASpeedFast Recovery =< 500ns, > 200mA (Io)SpeedSunsCurrent - Reverse Leakage @ Vr500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMASupplier Device PackageSupplier Device PackageSupplier Device PackageSupplier Device Package </th <th></th> <th></th>		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C	Manufacturer Part Number	RS1KLHM2G
Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Jo)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) 800 MAVoltage - Forward (Vf) (Max) @ If $1.3V @ 800$ MASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr) 500 nsCurrent - Reverse Leakage @ Vr $5\mu A @ 800V$ Capacitance @ Vr, F $10pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction $55^{\circ}C ~ 150^{\circ}C$	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io) $800mA$ Voltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5µA @ 800V$ Capacitance @ Vr, F $10pF @ 4V, 1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction $55°C ~ 150°C$		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max) $800V$ Current - Average Rectified (Io) $800mA$ Voltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5\muA @ 800V$ Capacitance @ Vr, F $10pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction $-55°C ~ 150°C$	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.3V @ 800mA$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5\mu A @ 800V$ Capacitance @ Vr, F $10pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150° C	Voltage - DC Reverse (Vr) (Max)	800V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr $5\mu A @ 800V$ Capacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	800mA
Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 800mA
Current - Reverse Leakage @ Vr5μA @ 800VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	500ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 800V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	10pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Deposit environ	Operating Temperature - Junction	$-55^{\circ}C \sim 150^{\circ}C$
Keport error		Report errors?

RS1KLHM2G Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RS1KLHM2G Payment Methods



RS1KLHM2G Shipping Methods



If you have any question about RS1KLHM2G, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com