

RS1ML MTG

RS1ML MTG Information

Heisener.com	 RS1ML MTG TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, FAST, 0.8A, 1000V, 500NS, DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RS1ML MTG Specifications

ManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMouning TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	RS1ML MTG
Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Jo)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	-
Current - Average Rectified (Io)800mAVoltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.3V @ 800mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	-
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	800mA
Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 800mA
Current - Reverse Leakage @ Vr5μA @ 1000VCapacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F10pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	500ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5μA @ 1000V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	10pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

RS1ML MTG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RS1ML MTG Payment Methods



RS1ML MTG Shipping Methods



If you have any question about RS1ML MTG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com