

# RSC13DRTH-S734

## **RSC13DRTH-S734 Information**

Heisener.com Distai service statis tiere	 RSC13DRTH-S734 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 26POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RSC13DRTH-S734 Specifications**

ManufacturerSullins Connector SolutionsCardegoryConnectors, Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions/Bay/Row26Card Tytek0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Number of Rows3.010" (2.54mm)Features-Mounting TypeMong HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact TypeFul BellowsContact TypeSolderContact SpecifiesSolderContact Finish ThicknessSolderContact SpecifiesSolderContact SpecifiesSolder		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions/Bay/Row26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness0.04Contact TypeGoldContact TypeFull BellowsColorGreenFlage Feature-Operating Temperature-Soler ~ 125°C-	Manufacturer Part Number	RSC13DRTH-S734
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Sumber of Positions26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature- Top Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Card Thickness0.031" (0.79mm)Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness6oldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65° < 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-Operating Temperature- <td>Package</td> <td>-</td>	Package	-
GenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row13Number of Positions26Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOloo (2.54mm)Contact MaterialSolderContact FinishGoldContact TypeIupin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 26   Card Thickness 0.031" (0.79mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Through Hole   Cortact Material Solder   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Type Full Bellows   Color Green   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	13
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	26
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.031" (0.79mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessI/lµin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **RSC13DRTH-S734** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RSC13DRTH-S734** Payment Methods





If you have any question about RSC13DRTH-S734, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com