

# **RSFAL MHG**

### **RSFAL MHG Information**

Heisener.com	 RSFAL MHG TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, FAST, 0.5A, 50V, 150NS, S DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RSFAL MHG Specifications**

ManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSut SMA		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	RSFAL MHG
Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Jo)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series-SeriesStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr\$µA @ 50VCurrent - Reverse Leakage @ Vr\$µA @ 50VCurrent - Reverse Leakage @ Vr\$µF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5 $\mu$ A @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	-
Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.3V @ 500mA$ SpeedFast Recovery =< $500ns$ , > $200mA$ (Io)Reverse Recovery Time (trr) $150ns$ Current - Reverse Leakage @ Vr $5\muA @ 50V$ Capacitance @ Vr, F $4pF @ 4V$ , $1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction $-55^\circ$ C ~ $150^\circ$ C	Voltage - DC Reverse (Vr) (Max)	50V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	500mA
Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 500mA
Current - Reverse Leakage @ Vr5μA @ 50VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	150ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 50V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	4pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

#### **RSFAL MHG Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **RSFAL MHG Payment Methods**



# **RSFAL MHG Shipping Methods**



If you have any question about RSFAL MHG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com