

RSFGLHRVG

RSFGLHRVG Information

Heisener.com	 RSFGLHRVG TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, FAST, 0.5A, 400V, 150NS, DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RSFGLHRVG Specifications

Manufacturer Part NumberRSFGLHRVGManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - SinglePackageAutomotive, AEC-Q101SeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCurrent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, FJorde MountMounting TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDo-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCurrent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, F5urface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C	Manufacturer Part Number	RSFGLHRVG
Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCurnent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, FSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55° < 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5 μ A @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55° C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max) $400V$ Current - Average Rectified (Io) $500mA$ Voltage - Forward (Vf) (Max) @ If $1.3V @ 500mA$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $150ns$ Current - Reverse Leakage @ Vr $5\muA @ 400V$ Capacitance @ Vr, F $4pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction $-55°C ~ 150°C$	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)400VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If $1.3V$ @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr 5μ A @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150°C	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.3V @ 500mA$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $150ns$ Current - Reverse Leakage @ Vr $5\mu A @ 400V$ Capacitance @ Vr, F $4pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150° C	Voltage - DC Reverse (Vr) (Max)	400V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	500mA
Reverse Recovery Time (trr)150nsCurrent - Reverse Leakage @ Vr5µA @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 500mA
Current - Reverse Leakage @ Vr5μA @ 400VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	150ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 400V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	4pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

RSFGLHRVG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RSFGLHRVG Payment Methods



RSFGLHRVG Shipping Methods



If you have any question about RSFGLHRVG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com