

RSFKLHRVG

RSFKLHRVG Information

Heisener.com	Part Number Manufacturer Category Description Package	RSFKLHRVG TSC America Inc. Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE, FAST, 0.5A, 800V, 500NS, DO-219AB For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RSFKLHRVG Specifications

Manufacturer TSC America Inc. Category Discrete Semiconductor Products Diodes - Rectifiers - Single Diodes - Rectifiers - Single Package DO-219AB Series Automotive, AEC-Q101 Diode Type Standard Voltage - DC Reverse (Vr) (Max) 800V Current - Average Rectified (Io) 500mA Voltage - Forward (Vf) (Max) @ If 1.3V @ 500mA Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 500ns Current - Reverse Leakage @ Vr 5µA @ 800V Capacitance @ Vr, F 4µF @ 4V, 1MHz Mounting Type Surface Mount Package / Case DO-219AB		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttrr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer Part Number	RSFKLHRVG
Diodes - Rectifiers - SinglePackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F5µF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
SeriesAutomotive, AEC-Q101Diode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCurrent - Reverse Leakage @ Vr5µA @ 800VPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)800VCurrent - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	Automotive, AEC-Q101
Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - DC Reverse (Vr) (Max)	800V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	500mA
Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 500mA
Current - Reverse Leakage @ Vr5μA @ 800VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	500ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 800V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	4pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction -55°C ~ 150°C	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

RSFKLHRVG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RSFKLHRVG Payment Methods



RSFKLHRVG Shipping Methods



If you have any question about RSFKLHRVG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com