

RSFML RUG

est a Quote

RSFML RUG Information

Heisener.com	Part Number	RSFML RUG	
	Manufacturer	TSC America Inc.	Г
	Category	Discrete Semiconductor Products Diodes - Rectifiers - Single	
	Description	DIODE, FAST, 0.5A, 1000V, 500NS,	- 7
	Package	DO-219AB	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RSFML RUG Specifications

ManufacturerTSC America Inc.CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSut SMA		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, FSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction55°C ~ 150°C	Manufacturer Part Number	RSFML RUG
Diodes - Rectifiers - SinglePackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Jo)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, FSurface MountMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Manufacturer	TSC America Inc.
PackageDO-219ABSeries-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Series-Diode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr\$µA @ 1000VCurrent - Reverse Leakage @ Vr\$µF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDo-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeStandardDiode TypeStandardVoltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCurrent - Reverse Leakage @ Vr4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Package	DO-219AB
Voltage - DC Reverse (Vr) (Max)-Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Series	-
Current - Average Rectified (Io)500mAVoltage - Forward (Vf) (Max) @ If1.3V @ 500mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If $1.3V @ 500mA$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr) $500ns$ Current - Reverse Leakage @ Vr $5\mu A @ 1000V$ Capacitance @ Vr, F $4pF @ 4V$, $1MHz$ Mounting TypeSurface MountPackage / Case $DO-219AB$ Supplier Device PackageSub SMAOperating Temperature - Junction -55° C ~ 150° C	Voltage - DC Reverse (Vr) (Max)	-
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Average Rectified (Io)	500mA
Reverse Recovery Time (trr)500nsCurrent - Reverse Leakage @ Vr5μA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	1.3V @ 500mA
Current - Reverse Leakage @ Vr5µA @ 1000VCapacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F4pF @ 4V, 1MHzMounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Reverse Recovery Time (trr)	500ns
Mounting TypeSurface MountPackage / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Current - Reverse Leakage @ Vr	5µA @ 1000V
Package / CaseDO-219ABSupplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Capacitance @ Vr, F	4pF @ 4V, 1MHz
Supplier Device PackageSub SMAOperating Temperature - Junction-55°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	Package / Case	DO-219AB
	Supplier Device Package	Sub SMA
Report errors?	Operating Temperature - Junction	-55°C ~ 150°C
		Report errors?

RSFML RUG Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RSFML RUG Payment Methods



RSFML RUG Shipping Methods



If you have any question about RSFML RUG, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com