

RSN-400-100B Information

Part Number RSN-400-100B

Manufacturer Riedon Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 0.00025 OHM 40W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RSN-400-100B Specifications

Manufacturer Part Number RSN-400-100B Manufacturer Riedon Category Resistors Package Rectangular Case Series RSN Resistance 250 μOhms Tolerance ±0.1% Power (Watts) 40W Composition Metal Element Temperature Coefficient ±15ppm/°C Operating Temperature 30°C ~ 70°C Features Current Sense Coating, Housing Type - Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate - Report errors?		
CategoryResistorsPackageRectangular CaseSeriesRSNResistance250 µOhmsTolerance±0.1%Power (Watts)40WCompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Manufacturer Part Number	RSN-400-100B
Chassis Mount ResistorsPackageRectangular CaseSeriesRSNResistance250 μOhmsTolerance±0.1%Power (Watts)40WCompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Manufacturer	Riedon
PackageRectangular CaseSeriesRSNResistance250 μOhmsTolerance±0.1%Power (Watts)40WCompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Category	Resistors
SeriesRSNResistance $250 \mu\text{Ohms}$ Tolerance $\pm 0.1\%$ Power (Watts) $40W$ CompositionMetal ElementTemperature Coefficient $\pm 15 \text{ppm/°C}$ Operating Temperature $30^{\circ}\text{C} \sim 70^{\circ}\text{C}$ FeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension 6.000° L x 1.250° W (152.40mm x 31.75mm)Height - Seated (Max) 1.380° (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance250 μOhmsTolerance±0.1%Power (Watts)40WCompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Package	Rectangular Case
Tolerance ±0.1% Power (Watts) 40W Composition Metal Element Temperature Coefficient ±15ppm/°C Operating Temperature 30°C ~ 70°C Features Current Sense Coating, Housing Type - Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Series	RSN
Power (Watts)40WCompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Resistance	250 μOhms
CompositionMetal ElementTemperature Coefficient±15ppm/°COperating Temperature30°C ~ 70°CFeaturesCurrent SenseCoating, Housing Type-Mounting FeatureFlangesSize / Dimension6.000" L x 1.250" W (152.40mm x 31.75mm)Height - Seated (Max)1.380" (35.05mm)Lead Style-Package / CaseRectangular CaseFailure Rate-	Tolerance	±0.1%
Temperature Coefficient ±15ppm/°C Operating Temperature 30°C ~ 70°C Features Current Sense Coating, Housing Type - Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Power (Watts)	40W
Operating Temperature 30°C ~ 70°C Features Current Sense Coating, Housing Type - Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Composition	Metal Element
Features Coating, Housing Type - Mounting Feature Size / Dimension Height - Seated (Max) Lead Style Package / Case Failure Rate Current Sense Current Sense Current Sense Current Sense Current Sense Current Sense (Nas) Lead Style Flanges 1.380" (35.05mm) - Rectangular Case Failure Rate - Current Sense Failure Sense Failure Rate	Temperature Coefficient	±15ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Operating Temperature	30°C ~ 70°C
Mounting Feature Flanges Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Features	Current Sense
Size / Dimension 6.000" L x 1.250" W (152.40mm x 31.75mm) Height - Seated (Max) 1.380" (35.05mm) Lead Style - Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	-
Height - Seated (Max) Lead Style Package / Case Rectangular Case Failure Rate 1.380" (35.05mm) - Rectangular Case	Mounting Feature	Flanges
Lead Style-Package / CaseRectangular CaseFailure Rate-	Size / Dimension	6.000" L x 1.250" W (152.40mm x 31.75mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	1.380" (35.05mm)
Failure Rate -	Lead Style	-
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

RSN-400-100B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RSN-400-100B Payment Methods





















RSN-400-100B Shipping Methods













If you have any question about RSN-400-100B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com