

RT1432B6TR13

RT1432B6TR13 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RT1432B6TR13 Specifications

Manufacturer Part NumberRT1432B6TR13ManufacturerCTS Resistor ProductsCategoryResistorsPackageResistor Networks, ArraysPackageClearONE?Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins50mWOperating Temperature50mWOperating Temperature50°C ~ 125°CApplicationsDIA SDRAMMounting TypeSurface MountAuger Acade7.1BGASupplier Device Package7.1BGASize / Dimension19.6SORSize / Dimension6.05% °L 4.0150° W (11.43mm x 3.81mm)Height Seated (Max)0.05% °L 4.0150° W (11.43mm x 3.81mm)	-	
CategoryResistorsResistor Networks, ArraysPackage27-LBGASeriesClearONE?Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins27Power Per Element50mWOperating Temperature55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package57°G A (9x3)Size / Dimension0.058° (1.47mm)Height - Seated (Max)0.058° (1.47mm)	Manufacturer Part Number	RT1432B6TR13
Resistor Networks, ArraysPackage27-LBGASeriesClearONE?Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package57°G (9x3)Size / Dimension0.058" (1.47mm)Height - Seated (Max)0.058" (1.47mm)	Manufacturer	CTS Resistor Products
Package27-LBGASeriesClearONE?Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins7Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature55°C ~ 125°CApplicationsDDR SDRAMNounting TypeSurface MountPackage / Case27-LBGASupplier Device Package57°C N 13° (14.3mm x 3.81mm)Height - Seated (Max)0.58" (14.7mm)	Category	Resistors
SeriesClearONE?Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package57°C % % 11.43mm x 3.81mm)Height - Seated (Max)0.058″ (1.47mm)		Resistor Networks, Arrays
Circuit TypeDual TerminatorResistance (Ohms)120Tolerance±1%Number of Resistors18Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASuppler Device Package0.450° L x 0.150° W (11.43mm x 3.81mm)Height - Seated (Max)0.55% (1.47mm)	Package	27-LBGA
Resistance (Ohms) 120 Tolerance ±1% Number of Resistors 18 Number of Pins 27 Power Per Element 50mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications DDR SDRAM Mounting Type Surface Mount Package / Case 27-LBGA Supplier Device Package 0.450" L x 0.150" W (11.43mm x 3.81mm) Height - Seated (Max) 0.058" (1.47mm)	Series	ClearONE?
Tolerance±1%Number of Resistors18Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Circuit Type	Dual Terminator
Number of Resistors18Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package0.450° L x 0.150° W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Resistance (Ohms)	120
Number of Pins27Power Per Element50mWTemperature Coefficient±200pm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Tolerance	$\pm 1\%$
Power Per Element50mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Number of Resistors	18
Temperature Coefficient±200pm/°COperating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Number of Pins	27
Operating Temperature-55°C ~ 125°CApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Power Per Element	50mW
ApplicationsDDR SDRAMMounting TypeSurface MountPackage / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Temperature Coefficient	$\pm 200 ppm^{/\circ}C$
Mounting TypeSurface MountPackage / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Operating Temperature	-55°C ~ 125°C
Package / Case27-LBGASupplier Device Package27-BGA (9x3)Size / Dimension0.450" L x 0.150" W (11.43mm x 3.81mm)Height - Seated (Max)0.058" (1.47mm)	Applications	DDR SDRAM
Supplier Device Package 27-BGA (9x3) Size / Dimension 0.450" L x 0.150" W (11.43mm x 3.81mm) Height - Seated (Max) 0.058" (1.47mm)	Mounting Type	Surface Mount
Size / Dimension 0.450" L x 0.150" W (11.43mm x 3.81mm) Height - Seated (Max) 0.058" (1.47mm)	Package / Case	27-LBGA
Height - Seated (Max) 0.058" (1.47mm)	Supplier Device Package	27-BGA (9x3)
	Size / Dimension	0.450" L x 0.150" W (11.43mm x 3.81mm)
Report errors?	Height - Seated (Max)	0.058" (1.47mm)
		Report errors?

RT1432B6TR13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RT1432B6TR13 Payment Methods



RT1432B6TR13 Shipping Methods



If you have any question about RT1432B6TR13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com