

RT334024 Information



For Reference Only

Part Number RT334024

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RT334024 Specifications

Manufacturer Part Number RT334024 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT334024
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 16.7mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	RT1, SCHRACK
Coil Current Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	16.7mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	24VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) 2.4 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

RT334024 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RT334024 Payment Methods



















RT334024 Shipping Methods













If you have any question about RT334024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com