

RT33L048 Information



For Reference Only

Part Number RT33L048

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RT33L048 Specifications

Manufacturer RT33L048 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT1, Inrush, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 8.7 mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT1, Inrush, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT33L048
Package-SeriesRT1, Inrush, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRT1, Inrush, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesRT1, Inrush, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current8.7mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time9msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	RT1, Inrush, SCHRACK
Coil Current Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.7mA
Contact Rating (Current) Switching Voltage 400VAC - Max 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	48VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) 4.8 VDC Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 9ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	9ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
I .		Report errors?

RT33L048 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RT33L048 Payment Methods





















RT33L048 Shipping Methods













If you have any question about RT33L048, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com