

RT424F06 Information



For Reference Only

Part Number RT424F06

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPDT 8A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RT424F06 Specifications

Manufacturer RT424F06 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT2 Bistable, SCHRACK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 109mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT424F06
Package-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Dual Coil Coil Current 109mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	RT2 Bistable, SCHRACK
Coil Current109mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	109mA
Contact Rating (Current) Switching Voltage 400VAC - Max 4.2 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	6VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	4.2 VDC
Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
report errors.		Report errors?

RT424F06 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RT424F06 Payment Methods





















RT424F06 Shipping Methods













If you have any question about RT424F06, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com