

### **RT424F12 Information**



For Reference Only

Part Number RT424F12

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 8A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RT424F12 Specifications**

Manufacturer Part Number       RT424F12         Manufacturer       TE Connectivity Potter & Brumfield Relays         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       RT2 Bistable, SCHRACK         Relay Type       General Purpose         Coil Type       Latching, Dual Coil         Coil Current       50mA         Coil Voltage       12VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       8A         Switching Voltage       400VAC - Max         Turn On Voltage (Max)       8.4 VDC         Turn Off Voltage (Min)       -         Operate Time       10ms         Release Time       5ms         Features       Insulation - Class F, Sealed - Flux Protection         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT424F12
Package-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesRT2 Bistable, SCHRACKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	RT2 Bistable, SCHRACK
Coil Current50mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current) 8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max) 8.4 VDC  Turn Off Voltage (Min) - Operate Time 10ms  Release Time 5ms  Features Insulation - Class F, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	50mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  8.4 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	12VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 8.4 VDC  Turn Off Voltage (Min) -  Operate Time 10ms  Release Time 5ms  Features Insulation - Class F, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	400VAC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time 5ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Insulation - Class F, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **RT424F12 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **RT424F12 Payment Methods**



















### **RT424F12 Shipping Methods**













If you have any question about RT424F12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com