

### **RT425005 Information**



For Reference Only

Part Number RT425005

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 8A 5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RT425005 Specifications**

Manufacturer Part Number       RT425005         Manufacturer       TE Connectivity Potter & Brumfield Relays         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       RT2, SCHRACK         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       80.6mA         Coil Voltage       5VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       8A         Switching Voltage       400VAC - Max         Turn On Voltage (Max)       3.5 VDC         Turn Off Voltage (Min)       0.5 VDC         Operate Time       8ms         Release Time       6ms         Features       Insulation - Class F, Sealed - Flux Protection         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPackage-SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT425005
Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 80.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style Permination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         RT2, SCHRACK           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         80.6mA           Coil Voltage         5VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC - Max           Turn On Voltage (Max)         3.5 VDC           Turn Off Voltage (Min)         0.5 VDC           Operate Time         8ms           Release Time         6ms           Features         Insulation - Class F, Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80.6mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 80.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	RT2, SCHRACK
Coil Current 80.6mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  8A  Switching Voltage 400VAC - Max  Turn On Voltage (Max)  3.5 VDC  Turn Off Voltage (Min)  0.5 VDC  Operate Time  8ms  Release Time  6ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Current	80.6mA
Contact Rating (Current)  Switching Voltage  400VAC - Max  Turn On Voltage (Max)  3.5 VDC  Turn Off Voltage (Min)  Operate Time  8ms  Release Time  6ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	5VDC
Switching Voltage 400VAC - Max  Turn On Voltage (Max) 3.5 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 8ms  Release Time 6ms  Features Insulation - Class F, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  8ms  Release Time  6ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  3.5 VDC  8ms  Function  8ms  Features  Features  Insulation - Class F, Sealed - Flux Protection  Through Hole  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  8ms  Release Time  6ms  Features  Insulation - Class F, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 6ms Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Insulation - Class F, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **RT425005 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RT425005 Payment Methods**





















## **RT425005 Shipping Methods**













If you have any question about RT425005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com