

RT444615 Information



For Reference Only

Part Number RT444615

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 8A 115V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RT444615 Specifications

Manufacturer Part Number RT444615 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormDPST (2 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RT444615
Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 115VAC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Category	Relays
SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormDPST (2 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage115 VACContact FormDPST (2 Form A)Contact Rating (Current)8ASwitching Voltage400 VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current-Coil Voltage115VACContact FormDPST (2 Form A)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	RT2, SCHRACK
Coil Current Coil Voltage 115VAC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Release Time Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	115VAC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style 86.3 VAC - Insulation - Class F, Sealed - Flux Protection	Contact Rating (Current)	8A
Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time - Release Time - Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	86.3 VAC
Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	17.3 VAC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

RT444615 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RT444615 Payment Methods





















RT444615 Shipping Methods













If you have any question about RT444615, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com