

RTB34730 Information

Heisener.com

Part Number RTB34730

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 12A 230V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RTB34730 Specifications

Manufacturer Part NumberRTB34730ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RTB34730
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 230VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	RT1, SCHRACK
Coil Current-Coil Voltage230VACContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)172.5 VACTurn Off Voltage (Min)34.5 VACOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 230VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	230VAC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 172.5 VAC Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	12A
Turn Off Voltage (Min) 34.5 VAC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	172.5 VAC
Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	34.5 VAC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

RTB34730 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RTB34730 Payment Methods



















RTB34730 Shipping Methods













If you have any question about RTB34730, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com