



RTB74005 Information



For Reference Only

Part Number RTB74005

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RTB74005 Specifications

Manufacturer Part NumberRTB74005ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	RTB74005
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Turnout Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Trhrough Hole	Category	Relays
SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Series	RT1, SCHRACK
Coil Current50mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage400VAC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Current	50mA
Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Coil Voltage	5VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Switching Voltage	400VAC - Max
Operate Time10msRelease Time8msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	3.75 VDC
Release Time 8ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	0.5 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	8ms
	Features	Insulation - Class F, Sealed - Fully
m to do on the poor	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

RTB74005 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RTB74005 Payment Methods


































If you have any question about RTB74005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com