



RTD14006 Information

Heisener.com

Part Number RTD14006

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 16A 6V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RTD14006 Specifications

Manufacturer Part Number RTD14006 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	RTD14006
Package-SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RT1, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesRT1, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	RT1, SCHRACK
Coil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage400VAC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class F, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 400VAC - Max 42 VDC Turn Off Voltage (Min) Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style 16A 400VAC - Max 4.2 VDC 0.6 VDC 0ms 1mulation - Class F, Sealed - Fully Through Hole PC Pin	Coil Voltage	6VDC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	400VAC - Max
Operate Time 8ms Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.2 VDC
Release Time 6ms Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class F, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F, Sealed - Fully
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

RTD14006 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RTD14006 Payment Methods



















RTD14006 Shipping Methods













If you have any question about RTD14006, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com