

### **RTX3-1AT-B024 Information**



For Reference Only

Part Number RTX3-1AT-B024

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 16A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **RTX3-1AT-B024 Specifications**

Manufacturer Part Number  Manufacturer  TE Connectivity Potter & Brumfield Relays  Relays  Power Relays, Over 2 Amps  Package  - Series  RTX, SCHRACK  Relay Type  General Purpose  Coil Type  Latching, Single Coil  Coil Current  27mA  Coil Voltage  24VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  16A  Switching Voltage  18 VDC  Turn On Voltage (Max)  Turn On Voltage (Min)  Operate Time  Pales of Time		
Category  Relays  Power Relays, Over 2 Amps  Package  - Series  RTX, SCHRACK  Relay Type  General Purpose  Coil Type  Latching, Single Coil  Coil Current  27mA  Coil Voltage  24VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  16A  Switching Voltage  250VAC - Nom  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  -  Relays  Power Relays, Over 2 Amps  Power Relays Amps  Power Relays Amps  Power Relays Amps  Power Relays Amps	Manufacturer Part Number	RTX3-1AT-B024
Package - Series RTX, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 27mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage Max) 18 VDC Turn Off Voltage (Min) - Operate Time -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - RTX, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 27mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time -	Category	Relays
Series RTX, SCHRACK Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 27mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time -		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Latching, Single Coil  Coil Current 27mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -	Package	-
Coil Type Latching, Single Coil Coil Current 27mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC - Nom Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time -	Series	RTX, SCHRACK
Coil Current27mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC - NomTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-	Relay Type	General Purpose
Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -	Coil Type	Latching, Single Coil
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -	Coil Current	27mA
Contact Rating (Current)  Switching Voltage  250VAC - Nom  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  -	Coil Voltage	24VDC
Switching Voltage 250VAC - Nom  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  -	Contact Rating (Current)	16A
Turn Off Voltage (Min)  Operate Time  -	Switching Voltage	250VAC - Nom
Operate Time -	Turn On Voltage (Max)	18 VDC
	Turn Off Voltage (Min)	-
Delegar Time	Operate Time	-
Release Time -	Release Time	-
Features Insulation - Class F	Features	Insulation - Class F
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **RTX3-1AT-B024 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **RTX3-1AT-B024 Payment Methods**





















## **RTX3-1AT-B024** Shipping Methods













If you have any question about RTX3-1AT-B024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com