



RUB0J151MLG Information



For Reference Only

Part Number RUB0J151MLG

Manufacturer Nichicon Category Capacitors

Aluminum - Polymer Capacitors

Description CAP ALUM POLY 150UF 20% 6.3V SMD

Package 2917 (7343 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RUB0J151MLG Specifications

Manufacturer Part Number RUB0J151MLG Manufacturer Nichicon Category Capacitors Aluminum - Polymer Capacitors Package 2917 (7343 Metric) Series FPCAP, UB Type Polymer Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)		
Category Capacitors Package 2917 (7343 Metric) Series FPCAP, UB Type Polymer Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Manufacturer Part Number	RUB0J151MLG
PackageAluminum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesFPCAP, UBTypePolymerCapacitance150μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)15 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Surface Mount Land Size-Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Manufacturer	Nichicon
Package 2917 (7343 Metric) Series FPCAP, UB Type Polymer Capacitance 150μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Category	Capacitors
Series FPCAP, UB Type Polymer Capacitance 150µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)		Aluminum - Polymer Capacitors
Type Polymer Capacitance 150μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Package	2917 (7343 Metric)
Capacitance 150μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 15 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Heigh - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Series	FPCAP, UB
Tolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)15 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Surface Mount Land Size-Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Type	Polymer
Voltage - Rated6.3VESR (Equivalent Series Resistance)15 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.079" (2.00mm)Surface Mount Land Size-Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Capacitance	150μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 105°C General Purpose - General Purpose - General Purpose - General Purpose - General Purpose - General Purpose - General Purpose - General Purpose - Occupanty - Surface Mount (7.30mm x 4.30mm) - Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Voltage - Rated	6.3V
Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	ESR (Equivalent Series Resistance)	15 mOhm
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing Size / Dimension - Height - Seated (Max) Surface Mount Land Size - Mounting Type Surface Mount Package / Case General Purpose - Cannother Surface Mount - C	Lifetime @ Temp.	1000 Hrs @ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Operating Temperature	-55°C ~ 105°C
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension O.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) O.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Surface Mount Package / Case 2917 (7343 Metric)	Ripple Current - High Frequency	-
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.079" (2.00mm) Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case 0.079" (2.00mm) - Surface Mount 2917 (7343 Metric)	Lead Spacing	-
Surface Mount Land Size - Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Height - Seated (Max)	0.079" (2.00mm)
Package / Case 2917 (7343 Metric)	Surface Mount Land Size	-
	Mounting Type	Surface Mount
Report errors?	Package / Case	2917 (7343 Metric)
		Report errors

RUB0J151MLG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RUB0J151MLG Payment Methods



















RUB0J151MLG Shipping Methods













If you have any question about RUB0J151MLG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com