

RWR81N1R65FSS70

RWR81N1R65FSS70 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RWR81N1R65FSS70 Specifications

Manufacturer Part NumberRWR81N1R65FSS70ManufacturerVishay DaleCategoryResistorsPackageAxialPackageAxialSeriesMilitary, MIL-PRF-39007, RWR81NResistance1.65 OhmsTolerance±1%Power (Wats)WCompositionWirewoundFeaturesMilitary, Milsure Resistant, Non-InductivePackage / CaseAxialSupplier Device PackageAxialSupplier Device PackageAxialHeight - Seated (Max)0.85° Dia x 0.250° L (2.16mm x 6.35mm)Height - Seated (Max)2Supplier Device Package5.00016%		
CategoryResistorsThrough Hole ResistorsPackageAxialSeriesMilitary, MIL-PRF-39007, RWR81NResistance1.65 OhmsTolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50ppm°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)2	Manufacturer Part Number	RWR81N1R65FSS70
Through Hole ResistorsPackageAxialPackageMilitary, MIL-PRF-39007, RWR81NResistance1.65 OhmsTolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50pm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)2	Manufacturer	Vishay Dale
PackageAxialSeriesMilitary, MIL-PRF-39007, RWR81NResistance1.65 OhmsTolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)2	Category	Resistors
SeriesMilitary, MIL-PRF-39007, RWR81NResistance1.65 OhmsTolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device Package0.085° Dia x 0.250° L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2		Through Hole Resistors
Resistance1.65 OhmsTolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device Package0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Package	Axial
Tolerance±1%Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductivePenperature Coefficient±50ppm°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device Package0.085° Dia x 0.250° L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Series	Military, MIL-PRF-39007, RWR81N
Power (Watts)IWCompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50pm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Resistance	1.65 Ohms
CompositionWirewoundFeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Tolerance	±1%
FeaturesMilitary, Moisture Resistant, Non-InductiveTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Power (Watts)	1W
Temperature Coefficient±50ppm/°COperating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Composition	Wirewound
Operating Temperature-55°C ~ 250°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Features	Military, Moisture Resistant, Non-Inductive
Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Temperature Coefficient	±50ppm/°C
Supplier Device PackageAxialSize / Dimension0.085" Dia x 0.250" L (2.16mm x 6.35mm)Height - Seated (Max)-Number of Terminations2	Operating Temperature	-55°C ~ 250°C
Number of Terminations0.085" Dia x 0.250" L (2.16mm x 6.35mm)Generation-Support of Terminations2	Package / Case	Axial
Height - Seated (Max)-Number of Terminations2	Supplier Device Package	Axial
Number of Terminations 2	Size / Dimension	0.085" Dia x 0.250" L (2.16mm x 6.35mm)
	Height - Seated (Max)	-
Evilure Pate $S(0.001\%)$	Number of Terminations	2
S (0.001%)	Failure Rate	S (0.001%)
Report errors ⁶		Report errors?

RWR81N1R65FSS70 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RWR81N1R65FSS70 Payment Methods





If you have any question about RWR81N1R65FSS70, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com