



RWS1500B48 Information



For Reference Only

Part Number RWS1500B48

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 1536W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RWS1500B48 Specifications

Manufacturer Part Number RWS1500B48 Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series RWS-B Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series RWS-B Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Manufacturer Part Number	RWS1500B48
Package - Series RWS-B Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package-SeriesRWS-BTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)32APower (Watts)1500WApplicationsITE (Commercial)Voltage - Isolation4kV (4000V)Efficiency88%Operating Temperature-20°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series RWS-B Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)		AC DC Converters
TypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)32APower (Watts)1500WApplicationsITE (Commercial)Voltage - Isolation4kV (4000V)Efficiency88%Operating Temperature-20°C ~ 60°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Series	RWS-B
Voltage - Input Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation Efficiency Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 88V Voltage - Isolation Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Type	Enclosed
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) 32A Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 1500W Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation $4kV$ (4000V) Efficiency 88% Operating Temperature $-20^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension $10.28^{\circ}\text{L x } 5.00^{\circ}\text{W x } 2.48^{\circ}\text{H } (261.0\text{mm x } 127.0\text{mm x } 63.0\text{mm})$	Current - Output (Max)	32A
Voltage - Isolation 4kV (4000V) Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Power (Watts)	1500W
Efficiency 88% Operating Temperature -20°C ~ 60°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Applications	ITE (Commercial)
Operating Temperature -20°C ~ 60°C (With Derating) Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Efficiency	88%
Mounting Type Chassis Mount Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Operating Temperature	-20°C ~ 60 °C (With Derating)
Size / Dimension 10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)	Features	Adjustable Output, DC Input Capable, PFC, Remote Sense, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	10.28" L x 5.00" W x 2.48" H (261.0mm x 127.0mm x 63.0mm)
		Report errors?

RWS1500B48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RWS1500B48 Payment Methods



















RWS1500B48 Shipping Methods













If you have any question about RWS1500B48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com