

### **RXE090 Information**



For Reference Only

Part Number RXE090

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

**Description** POLYSWITCH RXE SERIES 0.90A HOLD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **RXE090 Specifications**

Manufacturer Part Number         RXE090           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           PTC Resettable Fuses           Package         Radial, Disc           Series         PolySwitch?, RXE           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         900mA           Current - Trip (It)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)		
Category         Circuit Protection           Package         Radial, Disc           Series         PolySwitch?, RXE           Type         Polymeric           Voltage - Max         72 V           Current - Max         40 A           Current - Hold (lh) (Max)         900mA           Current - Trip (lt)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)	Manufacturer Part Number	RXE090
Package         Radial, Disc           Series         PolySwitch?, RXE           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         900mA           Current - Trip (It)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)	Manufacturer	Littelfuse Inc.
Package         Radial, Disc           Series         PolySwitch?, RXE           Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         900mA           Current - Trip (It)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)	Category	Circuit Protection
Series         PolySwitch?, RXE           Type         Polymeric           Voltage - Max         72 V           Current - Max         40 A           Current - Hold (Ih) (Max)         900mA           Current - Trip (It)         1.8 A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)		PTC Resettable Fuses
Type         Polymeric           Voltage - Max         72V           Current - Max         40A           Current - Hold (Ih) (Max)         900mA           Current - Trip (It)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)	Package	Radial, Disc
Voltage - Max         72V           Current - Max         40A           Current - Hold (lh) (Max)         900mA           Current - Trip (It)         1.8A           Time to Trip         7.2s           Resistance - Initial (Ri) (Min)         200 mOhms           Resistance - Post Trip (R1) (Max)         470 mOhms           Resistance - 25°C (Typ)         -           Operating Temperature         -           Ratings         -           Mounting Type         Through Hole           Package / Case         Radial, Disc           Size / Dimension         0.441" Dia x 0.118" W (11.20mm x 3.00mm)           Height - Seated (Max)         0.622" (15.80mm)           Thickness (Max)         -           Lead Spacing         0.199" (5.05mm)	Series	PolySwitch?, RXE
Current - Max       40A         Current - Hold (Ih) (Max)       900mA         Current - Trip (It)       1.8A         Time to Trip       7.2s         Resistance - Initial (Ri) (Min)       200 mOhms         Resistance - Post Trip (R1) (Max)       470 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.441" Dia x 0.118" W (11.20mm x 3.00mm)         Height - Seated (Max)       0.622" (15.80mm)         Thickness (Max)       -         Lead Spacing       0.199" (5.05mm)	Туре	Polymeric
Current - Hold (Ih) (Max)       900mA         Current - Trip (It)       1.8A         Time to Trip       7.2s         Resistance - Initial (Ri) (Min)       200 mOhms         Resistance - Post Trip (R1) (Max)       470 mOhms         Resistance - 25°C (Typ)       -         Operating Temperature       -         Ratings       -         Mounting Type       Through Hole         Package / Case       Radial, Disc         Size / Dimension       0.441" Dia x 0.118" W (11.20mm x 3.00mm)         Height - Seated (Max)       0.622" (15.80mm)         Thickness (Max)       -         Lead Spacing       0.199" (5.05mm)	Voltage - Max	72V
Current - Trip (It) Time to Trip 7.2s  Resistance - Initial (Ri) (Min) 200 mOhms  Resistance - Post Trip (R1) (Max) 470 mOhms  Resistance - 25°C (Typ) - Operating Temperature - Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing  1.8A 7.2s 1.8A 7.2s 1.8A 1.8A 1.8A 1.8A 1.8A 1.8A 1.8A 1.8A	Current - Max	40A
Time to Trip  Resistance - Initial (Ri) (Min)  Resistance - Post Trip (R1) (Max)  Resistance - 25°C (Typ)  Operating Temperature  Ratings  - Mounting Type  Through Hole  Package / Case  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  7.2s  470 mOhms  -  -  Radial, Disc  1.20  Radial, Disc  Radial, Disc  1.20  1	Current - Hold (Ih) (Max)	900mA
Resistance - Initial (Ri) (Min)  Resistance - Post Trip (R1) (Max)  470 mOhms  Resistance - 25°C (Typ)  - Operating Temperature  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  0.441" Dia x 0.118" W (11.20mm x 3.00mm)  Height - Seated (Max)  Thickness (Max)  - Lead Spacing  0.199" (5.05mm)	Current - Trip (It)	1.8A
Resistance - Post Trip (R1) (Max)  Resistance - 25°C (Typ)  Operating Temperature  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  470 mOhms  470 mO	Time to Trip	7.2s
Resistance - 25°C (Typ)  Operating Temperature  Ratings  - Mounting Type  Through Hole  Package / Case  Radial, Disc  Size / Dimension  0.441" Dia x 0.118" W (11.20mm x 3.00mm)  Height - Seated (Max)  Thickness (Max)  - Lead Spacing  0.199" (5.05mm)	Resistance - Initial (Ri) (Min)	200 mOhms
Operating Temperature  Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.622" (15.80mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Resistance - Post Trip (R1) (Max)	470 mOhms
Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.622" (15.80mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Resistance - 25°C (Typ)	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.622" (15.80mm)  Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Operating Temperature	-
Package / Case Radial, Disc Size / Dimension 0.441" Dia x 0.118" W (11.20mm x 3.00mm) Height - Seated (Max) 0.622" (15.80mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Ratings	-
Size / Dimension       0.441" Dia x 0.118" W (11.20mm x 3.00mm)         Height - Seated (Max)       0.622" (15.80mm)         Thickness (Max)       -         Lead Spacing       0.199" (5.05mm)	Mounting Type	Through Hole
Height - Seated (Max)       0.622" (15.80mm)         Thickness (Max)       -         Lead Spacing       0.199" (5.05mm)	Package / Case	Radial, Disc
Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Size / Dimension	0.441" Dia x 0.118" W (11.20mm x 3.00mm)
Lead Spacing 0.199" (5.05mm)	Height - Seated (Max)	0.622" (15.80mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.199" (5.05mm)
		Report errors's

### **RXE090 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **RXE090 Payment Methods**





















### **RXE090 Shipping Methods**













If you have any question about RXE090, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com