

RXEF135-1 Information



For Reference Only

Part Number RXEF135-1

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description POLYSWITCH PTC RESET 1.35A HOLD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









RXEF135-1 Specifications

Manufacturer Part Number RXEF135-1 Manufacturer Littelfuse Inc. Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series PolySwitch?, RXEF Type Polymeric Voltage - Max 72V Current - Max 40A Current - Hold (lh) (Max) 1.35A Current - Trip (lt) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Opcrating Temperature -40°C ~ 85°C Ratings - Mounting Type Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	THILL ICC I Specifications	
Category Circuit Protection Package Radial, Disc Scries PolySwitch?, RXEF Type Polymeric Voltage - Max 72V Current - Max 40A Current - Hold (Ih) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Manufacturer Part Number	RXEF135-1
Package Radial, Disc Series PolySwitch?, RXEF Type Polymeric Voltage - Max 72V Current - Max 40A Current - Hold (Ih) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Manufacturer	Littelfuse Inc.
Package Radial, Disc Series PolySwitch?, RXEF Type Polymeric Voltage - Max 72V Current - Max 40A Current - Hold (lh) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Category	Circuit Protection
Series PolySwitch?, RXEF Type Polymeric Voltage - Max 72 V Current - Max 40 A Current - Hold (Ih) (Max) 1.35 A Current - Trip (It) 2.7 A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)		PTC Resettable Fuses
Type Polymeric Voltage - Max 72V Current - Max 40A Current - Hold (Ih) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Package	Radial, Disc
Voltage - Max 72V Current - Max 40A Current - Hold (lh) (Max) 1.35A Current - Trip (lt) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Series	PolySwitch?, RXEF
Current - Max 40A Current - Hold (Ih) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Type	Polymeric
Current - Hold (Ih) (Max) 1.35A Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Voltage - Max	72V
Current - Trip (It) 2.7A Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Current - Max	40A
Time to Trip 9.6s Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Current - Hold (Ih) (Max)	1.35A
Resistance - Initial (Ri) (Min) 120 mOhms Resistance - Post Trip (R1) (Max) 300 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Current - Trip (It)	2.7A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing 300 mOhms - -40°C ~ 85°C -40°C ~ 85°C	Time to Trip	9.6s
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Resistance - Initial (Ri) (Min)	120 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Resistance - Post Trip (R1) (Max)	300 mOhms
Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Resistance - 25°C (Typ)	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Radial, Disc Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Ratings	-
Size / Dimension 0.571" Dia x 0.118" W (14.50mm x 3.00mm) Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.752" (19.10mm) Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Package / Case	Radial, Disc
Thickness (Max) - Lead Spacing 0.199" (5.05mm)	Size / Dimension	0.571" Dia x 0.118" W (14.50mm x 3.00mm)
Lead Spacing 0.199" (5.05mm)	Height - Seated (Max)	0.752" (19.10mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.199" (5.05mm)
		Report errors?

RXEF135-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

RXEF135-1 Payment Methods





















RXEF135-1 Shipping Methods













If you have any question about RXEF135-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com