

RYM28DTMD-S189

RYM28DTMD-S189 Information

Heisener.com	 RYM28DTMD-S189 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 56POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



RYM28DTMD-S189 Specifications

Manufacturer Part NumberRYM28DTMD-S189ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions/Bay/Row56Card Thickness0.062° (1.57mm)Number of Rows2Pich0.156° (3.96mm)Features-Mounting TypeSolderContact FinishSolderContact FinishSolderContact FinishGuidContact Finish ThicknessGuid (3.05mm)Contact Finish ThicknessSolidon (3.05mm)Contact Finish ThicknesSolidon (3.05mm)<		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type5Contact MaterialSolderContact FinishGoldContact FinishGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessSolge BlowsContact Finish ThicknessSolge BlowsContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessSolge BlowsColarGrenaFining FeatureFinish Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	RYM28DTMD-S189
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColoarGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact FinishGoldContact Finish ThicknessSolin (0.76µm)Contact TypeIop BellowsColarSipin (0.76µm)Contact Finish ThicknessSolin (0.76µm)Colar TypeIop BellowsColar TypeFeanFeanSipin (0.76µm)Colar TypeFeanFinish ThicknessSipin (0.76µm)Colar TypeFeanFinish ThicknessSipin (0.76µm)Colar TypeFeanFinish ThicknessSipin (0.76µm)Colar TypeFeanColar TypeFeanColar TypeFeanColar TypeFeanColar TypeFeanColar TypeFeanColar TypeFeanFeanFeanColar TypeFeanColar TypeFean	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessJoin (0.76µm)Contact TypeLoop BellowsColorGreenFange FeaturesFinish Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Number of Rows0.156" (3.96mm)Features-Mounting TypeNon Shole KangeYong AttentionSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessJuji (0.76µm)Contact TypeLoop BellowsColorGreenFange FeatureFinish Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-
GenderFemaleNumber of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeaturesFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions/Bay/Row28Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type1hrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeaturesFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions56Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact FinishGoldContact Finish ThicknessGoldContact TypeLoop BellowsColorGreenFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	28
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJujn (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	56
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.156" (3.96mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze
Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
ColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows
	Color	Green
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
	Operating Temperature	-65°C ~ 125°C
Report errors?		Report errors?

RYM28DTMD-S189 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

RYM28DTMD-S189 Payment Methods



RYM28DTMD-S189 Shipping Methods



If you have any question about RYM28DTMD-S189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com