

# RZ01-1A4-D009

Quote

#### **RZ01-1A4-D009 Information**

			RZ01-1A4-D009 TE Connectivity Potter & Brumfield Relays	ns:
	www.heisener.com	Category	Relays Power Relays, Over 2 Amps	- 1.397
		Description	RELAY GEN PURPOSE SPST 12A 9V	- 2.28
		Package	-	
	17		For the pricing/inventory/lead time, please contact us	<b>11</b> ,32
	For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **RZ01-1A4-D009 Specifications**

ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage (Max)6.3 VDCTurn On Voltage (Max)0.9 VDCCurnent6.3 VDCSwitching Voltage (Max)6.3 VDCSurd Surd Surd Surd Surd Surd Surd Surd		
CategoryRelaysPower Relays, Over 2 AmpsPackagePackageSeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Manufacturer Part Number	RZ01-1A4-D009
Package-SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Category	Relays
SeriesRZ, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCOperate Time6msRelease TimefomsFeaturesInsulation - Class FMounting TypePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage (Max)6.3 VDCTurn On Voltage (Min)0.9 VDCOperate Time6.3 VDCRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Package	-
Coil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Series	RZ, SCHRACK
Coil Current44.4mACoil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypePC Pin	Relay Type	General Purpose
Coil Voltage9VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeFor PinPin Pin Pin Pin PinPin PinYen Pin PinPinYen PinPin	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HolePC Pin	Coil Current	44.4mA
Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HolePenination StylePC Pin	Coil Voltage	9VDC
Switching Yoltage400VAC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HolePC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleFermination StylePC Pin	Contact Rating (Current)	12A
Turn Off Voltage (Min)0.9 VDCOperate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	400VAC - Max
Operate Time8msRelease Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	6.3 VDC
Release Time6msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	0.9 VDC
FeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin	Operate Time	8ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	6ms
Termination Style PC Pin	Features	Insulation - Class F
· · ·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **RZ01-1A4-D009 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## RZ01-1A4-D009 Payment Methods



### **RZ01-1A4-D009** Shipping Methods



If you have any question about RZ01-1A4-D009, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com